

LWU501i Lens Throw Ratios Technical Reference Information

INTRODUCTION

The table on the following page details the information required to calculate the Lens Throw Ratios for the LWU501i projector.

LWU501i Lens Information

Lens	Throw Distance Formula		Vertical/Horizontal Offset	Diagonal Screen Sizes	
	Standard (Inches)	Metric (cm)		Standard (Inches)	Metric (cm)
0.80:1 (121-111104-01)	TD = 0.80 x W + 3.13"	TD = 0.80 x W + 7.94 cm	On Axis V	30" to 600"	76 to 1524 cm
			On Axis H		
1.17-1.76:1 Zoom (121-112105-01)	TDmin = 1.17 x W + 2.51"	TDmin = 1.17 x W + 6.38 cm	+122% / -40% V	30" to 600"	76 to 1524 cm
	TDmax = 1.76 x W + 2.46"	TDmax = 1.76 x W + 6.25 cm	± 23% H		
1.50-3.00:1 Zoom (121-113106-01) (included)	TDmin = 1.50 x W + 1.81"	TDmin = 1.50 x W + 4.60 cm	+122% / -40% V	30" to 600"	76 to 1524 cm
	TDmax = 3.00 x W + 2.15"	TDmax = 3.00 x W + 5.47 cm	± 23% H		
2.80-4.90:1 Zoom (121-114107-01)	TDmin = 2.80 x W + 2.06"	TDmin = 2.80 x W + 5.23 cm	+122% / -40% V	30" to 600"	76 to 1524 cm
	TDmax = 4.90 x W - 0.74"	TDmax = 4.90 x W - 1.87 cm	± 23% H		
4.67-8.00:1 Zoom (121-115108-01)	TDmin = 4.67 x W + 12.04"	TDmin = 4.67 x W + 30.57 cm	+122% / -40% V	30" to 600"	76 to 1524 cm
	TDmax = 8.00 x W + 10.30"	TDmax = 8.00 x W + 26.15 cm	± 23% H		

NOTES: **1)** Throw distance measured from the center of the front foot of the projector. **2)** Calculated throw distance (TD) values are subject to a ± 5% tolerance for individual lens variation. **3)** Calculated offset values are subject to a ± 7% centering tolerance.