The top half of the page features a complex, abstract background of overlapping, semi-transparent blue triangles and polygons in various shades of blue, creating a dynamic, crystalline effect. This pattern tapers off towards the bottom left, meeting a white background.

Technical Reference
020-101695-04

Boxer 4K

Status System

CHRISTIE®

NOTICES

COPYRIGHT AND TRADEMARKS

Copyright © 2019 Christie Digital Systems USA Inc. All rights reserved.

All brand names and product names are trademarks, registered trademarks or trade names of their respective holders.

GENERAL

Every effort has been made to ensure accuracy, however in some cases changes in the products or availability could occur which may not be reflected in this document. Christie reserves the right to make changes to specifications at any time without notice. Performance specifications are typical, but may vary depending on conditions beyond Christie's control such as maintenance of the product in proper working conditions. Performance specifications are based on information available at the time of printing. Christie makes no warranty of any kind with regard to this material, including, but not limited to, implied warranties of fitness for a particular purpose. Christie will not be liable for errors contained herein or for incidental or consequential damages in connection with the performance or use of this material. Manufacturing facilities in Canada and China are ISO 9001 certified. Manufacturing facilities in Canada are also ISO 14001 certified.

WARRANTY

Products are warranted under Christie's standard limited warranty, the complete details of which are available by contacting your Christie dealer or Christie. In addition to the other limitations that may be specified in Christie's standard limited warranty and, to the extent relevant or applicable to your product, the warranty does not cover:

- a. Problems or damage occurring during shipment, in either direction.
- b. Projector lamps (See Christie's separate lamp program policy).
- c. Problems or damage caused by use of a projector lamp beyond the recommended lamp life, or use of a lamp other than a Christie lamp supplied by Christie or an authorized distributor of Christie lamps.
- d. Problems or damage caused by combination of a product with non-Christie equipment, such as distribution systems, cameras, DVD players, etc., or use of a product with any non-Christie interface device.
- e. Problems or damage caused by the use of any lamp, replacement part or component purchased or obtained from an unauthorized distributor of Christie lamps, replacement parts or components including, without limitation, any distributor offering Christie lamps, replacement parts or components through the internet (confirmation of authorized distributors may be obtained from Christie).
- f. Problems or damage caused by misuse, improper power source, accident, fire, flood, lightning, earthquake or other natural disaster.
- g. Problems or damage caused by improper installation/alignment, or by equipment modification, if by other than Christie service personnel or a Christie authorized repair service provider.
- h. Problems or damage caused by use of a product on a motion platform or other movable device where such product has not been designed, modified or approved by Christie for such use.
- i. Problems or damage caused by use of a projector in the presence of an oil-based fog machine or laser-based lighting that is unrelated to the projector.
- j. For LCD projectors, the warranty period specified in the warranty applies only where the LCD projector is in "normal use" which means the LCD projector is not used more than 8 hours a day, 5 days a week.
- k. Except where the product is designed for outdoor use, problems or damage caused by use of the product outdoors unless such product is protected from precipitation or other adverse weather or environmental conditions and the ambient temperature is within the recommended ambient temperature set forth in the specifications for such product.
- l. Defects caused by normal wear and tear or otherwise due to normal aging of a product.

The warranty does not apply to any product where the serial number has been removed or obliterated. The warranty also does not apply to any product sold by a reseller to an end user outside of the country where the reseller is located unless (i) Christie has an office in the country where the end user is located or (ii) the required international warranty fee has been paid.

The warranty does not obligate Christie to provide any on site warranty service at the product site location.

PREVENTATIVE MAINTENANCE

Preventative maintenance is an important part of the continued and proper operation of your product. Failure to perform maintenance as required, and in accordance with the maintenance schedule specified by Christie, will void the warranty.


REGULATORY

The product has been tested and found to comply with the limits for a Class A digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the product is operated in a commercial environment. The product generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of the product in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at the user's own expense. Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment

CAN ICES-3 (A) / NMB-3 (A)

이 기기는 업무용(A급)으로 전자파적합등록을 한 기기이오니 판매자 또는 사용자는 이점을 주의하시기 바라며, 가정 외의 지역에서 사용하는 것을 목적으로 합니다.

ENVIRONMENTAL

The product is designed and manufactured with high-quality materials and components that can be recycled and reused. This symbol  means that electrical and electronic equipment, at their end-of-life, should be disposed of separately from regular waste. Please dispose of the product appropriately and according to local regulations. In the European Union, there are separate collection systems for used electrical and electronic products. Please help us to conserve the environment we live in!

Content

Boxer 4K status system.	4
Product documentation.	4
Related documentation.	4
Status system states.	5
Alarm Group (SST+ALRM?).	5
Configuration Group (SST+CONF?).	5
System Group (SST+SYST?).	6
Signal Group (SST+SIGN?).	12
Lamp Group (SST+LAMP?).	13
Version Group (SST+VERS?).	20
Temperature Group (SST+TEMP?).	22
Cooling Group (SST+COOL?).	25
Serial Group (SST+SERI?).	27

Boxer 4K status system

This guide contains information about the values and fault conditions that can be reported by the status system on Boxer 4K devices.

The status system provides an overview of the device at the current point in time. It contains a number of groups, which contain a set of status items. Each status item represents a component or sub-component of the system. Obtain specific details regarding a warning or error for a status item using the log system.

The numbers next to the status items in this guide correspond directly to the status item index within each group.



The device presents the information contained in this document in the language selected by the operator.

Product documentation

For installation, setup, and user information, see the product documentation available on the Christie Digital Systems USA Inc. website. Read all instructions before using or servicing this product.

Boxer 4K, Boxer 2K, Boxer 30

1. Access the documentation from the Christie website:
 - Go to <http://bit.ly/2mpf6QK> or <https://www.christiedigital.com/en-us/business/products/projectors/3-chip-dlp/boxer-series>
 - Scan the QR code using a QR code reader app on a smartphone or tablet.



2. On the product page, select the model and switch to the **Downloads** tab.

Related documentation




Additional information on the projector is available in the following documents.

- *Boxer 4K Installation and Setup Guide (P/N: 020-101902-XX)*
- *Boxer 4K User Guide (P/N: 020-101777-XX)*
- *Boxer Product Safety Guide (P/N: 020-101780-XX)*
- *Boxer 4K Service Guide (P/N: 020-101699-XX)*

- *Boxer 4K Serial Commands Guide (P/N: 020-101697-XX)*

Status system states

The status system has three states to indicate the health of the device.









	OK	No known issue
	Warning	A problem with this item should be addressed.
	Error	A problem with this item prevents the projector from properly displaying video or turning on the projector.

Alarm Group (SST+ALRM?)

Displays any status items in the warning or error state. This group contains a dynamic number of status items. If everything in the projector is OK, this group is empty.

Configuration Group (SST+CONF?)

The Configuration Group provides values and fault conditions for configuration-related items in Boxer 4K.

#	Status	State	Value	Description
0	Projector Model		<projector model>	Displays the model for the Boxer 4K projector.
			Unknown	Cannot retrieve the model information.
			Jig Mode	Reserved for engineering use.
1	Projector S/N		<serial number>	Displays the serial number of the projector.
			Unknown	The storage device containing the information is inaccessible or the data on the device is corrupted.
2	Output Resolution		<horizontal>x<vertical>	Displays the native output resolution of the projector.
3	Projector Build Date		<YYYY>/<MM>/<DD>	Displays the build date of the projector.
			Unknown	The storage device containing the information is inaccessible or the data on the device is corrupted.






















System Group (SST+SYST?)

The System Group provides values and fault conditions relating to the system and its health for Boxer 4K.









































Some of the lamp driver and memory module statuses listed below may not be applicable for your installation as the model of projector determines the number of lamps in the projector.











#	Status	State	Value	Description
0	Projector Hours		<hours>:<minutes>	Displays the total amount of time that the projector has been on (including warm up and cool down times).
			N/A	Cannot retrieve or update the value.
1	Pitch/Roll		<pitch value>/<roll value>	Displays the physical orientation of the projector: <ul style="list-style-type: none"> • A negative pitch means that the projector is pointing down. • A negative roll means the projector is tilted counter clockwise as seen from the rear.
			Communication Fault	Information is not available due to a hardware fault.
5	Lens Motor Horizontal-Axis		Calibrating	Currently calibrating the lens motor.
6	Lens Motor Vertical-Axis		Calibrated	The motor range has been properly calibrated.
7	Lens Motor Zoom- Axis		Unknown	The status of the motor is unknown because a problem occurred in the upstream communication path.
8	Lens Motor Focus- Axis		Uncalibrated	The range for the current lens has not been determined and/or the reported position on the axis may be inaccurate.
8	Lens Motor Focus- Axis		Failed	During reset or calibration, an error was detected related to the motor and/or sensor.
9	Built-In Self Test		N/A	The built-in self test has not been executed yet.
			Passed	The built-in self test completed successfully.
			Failed	The built-in self-test failed.
10	System ID Board		OK	The device has been properly detected and initialized.





#	Status	State	Value	Description
			Unknown	The status of the device is unknown.
			Communication Fault	Cannot communicate with the device.
			Invalid Data	The information on the device is missing or corrupted.
11	Housekeeping Board		OK	The device has been properly detected and initialized.
			Unknown	The status of the device is unknown.
			Detection Fault	Cannot read the device hardware information.
			Initialization Fault	Cannot properly initialize the device.
			Communication Fault	The device failed to respond or it provided a bad response to a command.
12	Keypad Display		Auto Detect	The projector is attempting to detect the presence of the IKB and PDS.
			Programming	Programming the device with the correct firmware.
			OK	The device has been properly detected and initialized.
			Detection Fault	Cannot detect the IKB and PDS.
			Unexpected Behavior	The device is not responding correctly.
			Upgrade Failed	The device failed to upgrade properly.
				
13	Power Supply		OK	The power supply has been properly detected and initialized.
			Unknown	The status of the power supply is unknown due to an upstream communication fault.
			Limited Mode	The power supply is running in limited power mode.
			Fan Problem	One or more of the power supply fans is not performing to specification.
			Overtemperature	The power supply is reporting an overtemperature event even though all fans are operational.
				

#	Status	State	Value	Description
			Overtemperature/Fan Problem	The power supply is reporting an overtemperature event and a fan problem.
			Communication Fault	Communication either timed out or an error occurred in the transmission/reception of data.
			Upgrade Failed	The power supply failed to upgrade or downgrade to the correct firmware version.
14	Lamp A1 Driver		OK	The device has been properly detected and initialized.
15	Lamp A2 Driver			
16	Lamp A3 Driver		Unknown	The status of the device is unknown.
17	Lamp B1 Driver			
18	Lamp B2 Driver		Communication Fault	A problem occurred communicating with the device.
19	Lamp B3 Driver			
			General Fault	The device is not behaving as expected.
			Upgrade Failed	Failed to upgrade the lamp driver to the correct firmware version.
			Overheat Protection	The lamp driver is overheating.
			Low Voltage	The lamp driver is not providing enough voltage to the lamp.
			High Voltage	The lamp driver is providing too much voltage to the lamp.
			DC Drive Error	The lamp driver stopped due to a DC drive error.
			Low Input Voltage	The lamp driver is not receiving enough power.
			Abnormal Voltage Surge	The lamp driver received an abnormal surge of power.
20	Lamp A1 Memory Module		OK	The device has been properly detected and initialized.
21	Lamp A2 Memory Module			
22	Lamp A3 Memory Module		Unknown	The status of the device is unknown because the communication path to the memory module is non-functional.
23	Lamp B1 Memory Module			
24	Lamp B2 Memory Module			
25	Lamp B3 Memory Module		Communication Fault	Cannot communicate with the device.
			Invalid Data	The information on the device is missing or corrupted.
26	Lamp Door		Closed	The lamp door is closed.

#	Status	State	Value	Description
			Unknown	The lamp door status is unknown because the housekeeping board cannot be communicated with. See the Housekeeping Board status item for details about the failure.
			Open	The lamp door is open.
27	Power Supply Input Voltage		<voltage>V	The incoming AC voltage into the power supply is OK.
			Unknown	The status of this output is unknown because the power supply cannot be communicated with.
			<voltage>V	The incoming AC voltage is out of range.
28	Spare Interlock		Closed	The interlock is closed.
			Unknown	The spare interlock status is unknown because the housekeeping board cannot be communicated with. See the Housekeeping Board status item for details about the failure.
			Open	The interlock is open.
29	Lens ID		Detected	The lens was detected.
			Unknown	The communication path to the lens is not working; therefore, the state is unknown.
			Not Detected	Cannot detect the lens.
30	Main Control Board		OK	The IMXB FPGA has been initialized at least once and is known to be OK.
			Unknown	The IMXB FPGA status is unknown because it has not been powered up yet.
			Initialization Fault	Cannot successfully program the IMXB FPGA.
32	Power Supply Output A1		OK	The device has been properly detected and initialized.
33	Power Supply Output A2			
34	Power Supply Output A3			
35	Power Supply Output B1			
36	Power Supply Output B2			
37	Power Supply Output B3			
			Unknown	The status of this output is unknown because the power supply cannot be communicated with.







#	Status	State	Value	Description
			Overcurrent Detected	The lamp driver/lamp on this output rail was drawing too much power.
38	Lamp Cartridge A		Detected	Successfully detected the lamp cartridge.
39	Lamp Cartridge B		Unknown	The status of the lamp cartridge is unknown because a problem exists with the housekeeping board.
			Not Detected	The lamp cartridge became undetected while the lamps were on.
			Not Detected	The lamp cartridge is undetected while the lamps are off.
40	Lamp A1 Memory Module Reader		OK	The device has been properly detected and initialized.
41	Lamp A2 Memory Module Reader		Unknown	The status of the device is unknown.
42	Lamp A3 Memory Module Reader		Unknown	The status of the device is unknown.
43	Lamp B1 Memory Module Reader		Unknown	The status of the device is unknown.
44	Lamp B2 Memory Module Reader		Communication Fault	Cannot communicate with the device.
45	Lamp B3 Memory Module Reader		Communication Fault	Cannot communicate with the device.
46	Status LED Board		OK	The status of the status LED board is OK.
			Unknown	The status of the status LED board cannot be determined because the backplane is nonfunctional.
			Communication Fault	Cannot communicate with the status LED board.
47	Side Panel NFCT		OK	The side panel NFCT is OK.
			Unknown	The side panel NFCT status is unknown because the IKB is non-functional.
			Communication Fault	Cannot write to or read from the side panel NFCT.
48	Backplane		Off	The backplane is in standby without any cached errors or warnings.
			OK	The backplane has been properly detected and initialized.
			Detection fault	The backplane hardware information cannot be read.
			Initialization fault	The backplane could not be properly initialized.
			Runtime fault	The backplane experienced an unrecoverable failure during runtime.

#	Status	State	Value	Description		
49	Image Processor		Off	The image processor is in standby without any cached errors or warnings.		
			OK	The image processor has been properly detected and initialized.		
			Detection fault	The image processor hardware information cannot be read.		
			Initialization fault	The image processor could not be properly initialized.		
			Runtime fault	The image processor experienced an unrecoverable failure during runtime.		
50	Formatter-Red		Off	The formatter is in standby without any cached errors or warnings.		
51	Formatter-Green		OK	The formatter has been properly detected and initialized.		
52	Formatter-Blue		Unknown	The formatter status cannot be determined due to an upstream issue.		
			Power Bad	The formatter detected an unexpected power glitch and has started the process of parking the DMD. This is often recoverable.		
			Detection fault	The formatter hardware cannot be read.		
			Initialization fault	The formatter could not be properly initialized.		
			Runtime fault	The formatter experienced an unrecoverable failure during runtime.		
			Failed to configure clock	During initialization the clock could not be configured.		
			Failed to program FPGA	During initialization programming the FPGA failed.		
			Memory calibration failed	During initialization an error occurred with memory calibration.		
			Communication fault	Cannot write to or read from the formatter board.		
53	Option Card 0		Off	The option card is in standby without any cached errors or warnings.		
54	Option Card 1			OK	The option card has been properly detected and initialized.	
55	Option Card 2				Not Present	An option card is not installed in this slot.
56	Option Card 3					
57	Option Card 4					

#	Status	State	Value	Description
			Unknown	The option card status cannot be determined due to an upstream issue.
			Detection fault	The option card hardware information cannot be read.
			Initialization fault	The option card could not be properly initialized.
			Runtime fault	The option card experienced an unrecoverable failure during runtime.

Signal Group (SST+SIGN?)

The Signal Group provides values and fault conditions relating to the video signal status for Boxer 4K.

#	Status	State	Value	Description
0	HDBaseT Input		N/A	Either the card is not present or the card does not have a single input port.
1	Card 0, Input 1		<input type> (No Signal)	No signal is detected. Where <input type> : {DP, HDMI, DVI, 3G-SDI}
2	Card 0, Input 2			
3	Card 0, Input 3			
4	Card 0, Input 4			
11	Card 1 - Input 1		<input type>, <active window>@ <v-sync rate> (<status>)	Where <input type> : {DP, HDMI, DVI, 3G-SDI} <active window> : <columns>x<rows> <v-sync rate> : the input frame rate, in Hz (##.##Hz) <status> : {"Master", "No signal", "Inactive", "Locked"}
12	Card 1 - Input 2			
21	Card 2 - Input 1			
22	Card 2 - Input 2			
31	Card 3 - Input 1			
32	Card 3 - Input 2			
41	Card 4 - Input 1			
42	Card 4 - Input 2			
			<input type> <active window> @ <v-sync rate> (<status>)	Where <input type> : {DP, HDMI, DVI, 3G-SDI} <active window> : <columns>x<rows> <v-sync rate> : the input frame rate, in Hz (##.##Hz) <status> : {"Unlocked", "Out of phase"}
50	Output Frequency		N/A	No video is being displayed.
			<rate>Hz	Where <rate> : the output frame rate, in Hertz

#	Status	State	Value	Description
				If the input frequency does not match the output frequency, Free Running @ XX.YYHz is displayed.
51	Frame Locked	<input type="checkbox"/>	N/A	No video is being displayed or an internal test pattern is being displayed.
		<input type="checkbox"/>	Locked	The output is locked to the selected input(s).
		<input type="checkbox"/>	Unlocked	The output is not locked to the selected input(s).
53	TSIC Connection	<input type="checkbox"/>	N/A	Either the card is not present or the card does not have a single input port.
		<input type="checkbox"/>	No Signal	No signal is detected.

Lamp Group (SST+LAMP?)
















The Lamp Group provides values and fault conditions for lamp-related items in Boxer 4K.

















Some of the lamp statuses listed below may not be applicable for your installation as the model of projector determines the number of lamps in the projector.

#	Status	State	Value	Description
0	Lamp A1 State	<input type="checkbox"/>	On	The lamp is on.
		<input type="checkbox"/>	Warming Up	The lamp is warming up.
		<input type="checkbox"/>	Off	The lamp is off.
		<input type="checkbox"/>	Cooling Down	The lamp is cooling down.
		<input type="checkbox"/>	Waiting to Strike	The lamp is cooling down but will turn on as soon as the cool down is complete.
		<input type="checkbox"/>	Failed to Strike	The lamp failed to strike.
		<input type="checkbox"/>	Lamp Off - Unknown	The lamp was on but extinguished unexpectedly.
		<input type="checkbox"/>	Lamp Off - Interlock	The lamp was on but turned off due to a tripped interlock.
		<input type="checkbox"/>	Lamp Off - Fan Failure	The lamp was on but turned off due to a bulb blower or reflector fan failure.

#	Status	Sta Value te	Description
1	Lamp A1 Hours	<input type="text"/>	<hours>:<minutes> (h:m) The total amount of time that the lamp has been on.
		<input type="text"/>	Unknown The lamp hours are unknown because the lamp memory module cannot be communicated with. See the Lamp A1 Memory Module status item for details of the failure.
		<input type="text"/>	<hours>:<minutes> (h:m) - Lamp is past expiry The lamp is running past its maximum number of hours.
3	Lamp A1 Installation Date	<input type="text"/>	<YYYY>/<MM>/<DD> Displays the date the lamp was installed.
		<input type="text"/>	Unknown The lamp installation date is unknown because the lamp memory module cannot be communicated with. See the Lamp A1 Memory Module status item for details of the failure.
4	Lamp A1 S/N	<input type="text"/>	<value> Displays the serial number of the installed lamp.
		<input type="text"/>	Unknown The lamp serial number is unknown because the lamp memory module cannot be communicated with. See the Lamp A1 Memory Module status item for details of the failure.
6	Lamp A1 Voltage	<input type="text"/>	<voltage>V Displays the voltage being applied to the lamp as reported by the lamp driver.
		<input type="text"/>	Unknown The lamp state is unknown because the lamp driver could not be communicated with. See the Lamp A1 Memory Module status item for details of the failure.
40	Lamp A2 State	<input type="text"/>	On The lamp is on.
		<input type="text"/>	Warming Up The lamp is warming up.
		<input type="text"/>	Off The lamp is off.
		<input type="text"/>	Cooling Down The lamp is cooling down.
		<input type="text"/>	Waiting to Strike The lamp is cooling down but will turn on as soon as the cool down is complete.
		<input type="text"/>	Failed to Strike The lamp failed to strike.

#	Status	State	Value	Description
			Lamp Off - Unknown	The lamp was on but extinguished unexpectedly.
			Lamp Off - Interlock	The lamp was on but turned off due to a tripped interlock.
			Lamp Off - Fan Failure	The lamp was on but turned off due to a bulb blower or reflector fan failure.
41	Lamp A2 Hours		<hours>:<minutes> (h:m)	The total amount of time that the lamp has been on.
			Unknown	The lamp hours are unknown because the lamp memory module cannot be communicated with. See the Lamp A2 Memory Module status item for details of the failure.
			<hours>:<minutes> (h:m) - Lamp is past expiry	The lamp is running past its maximum number of hours.
43	Lamp A2 Installation Date		<YYYY>/<MM>/<DD>	Displays the date the lamp was installed.
			Unknown	The lamp installation date is unknown because the lamp memory module cannot be communicated with. See the Lamp A2 Memory Module status item for details of the failure.
44	Lamp A2 S/N		<value>	Displays the serial number of the installed lamp.
			Unknown	The lamp serial number is unknown because the lamp memory module cannot be communicated with. See the Lamp A2 Memory Module status item for details of the failure.
46	Lamp A2 Voltage		<voltage>V	Displays the voltage being applied to the lamp as reported by the lamp driver.
			Unknown	The lamp state is unknown because the lamp driver could not be communicated with. See the Lamp A2 Memory Module status item for details of the failure.
50	Lamp A3 State		On	The lamp is on.
			Warming Up	The lamp is warming up.
			Off	The lamp is off.

#	Status	State	Value	Description
			Cooling Down	The lamp is cooling down.
			Waiting to Strike	The lamp is cooling down but will turn on as soon as the cool down is complete.
			Failed to Strike	The lamp failed to strike.
			Lamp Off - Unknown	The lamp was on but extinguished unexpectedly.
			Lamp Off - Interlock	The lamp was on but turned off due to a tripped interlock.
			Lamp Off - Fan Failure	The lamp was on but turned off due to a bulb blower or reflector fan failure.
51	Lamp A3 Hours		<hours>:<minutes> (h:m)	The total amount of time that the lamp has been on.
			Unknown	The lamp hours are unknown because the lamp memory module cannot be communicated with. See the Lamp A3 Memory Module status item for details of the failure.
			<hours>:<minutes> (h:m) - Lamp is past expiry	The lamp is running past its maximum number of hours.
53	Lamp A3 Installation Date		<YYYY>/<MM>/<DD>	Displays the date the lamp was installed.
			Unknown	The lamp installation date is unknown because the lamp memory module cannot be communicated with. See the Lamp A3 Memory Module status item for details of the failure.
54	Lamp A3 S/N		<value>	Displays the serial number of the installed lamp.
			Unknown	The lamp serial number is unknown because the lamp memory module cannot be communicated with. See the Lamp A3 Memory Module status item for details of the failure.
56	Lamp A3 Voltage		<voltage>V	Displays the voltage being applied to the lamp as reported by the lamp driver.
			Unknown	The lamp state is unknown because the lamp driver could not be communicated with. See the Lamp A3 Memory Module status item for details of the failure.

#	Status	Sta Value	Description
60	Lamp B1 State	<input type="checkbox"/> On	The lamp is on.
		<input type="checkbox"/> Warming Up	The lamp is warming up.
		<input type="checkbox"/> Off	The lamp is off.
		<input type="checkbox"/> Cooling Down	The lamp is cooling down.
		<input type="checkbox"/> Waiting to Strike	The lamp is cooling down but will turn on as soon as the cool down is complete.
		<input checked="" type="checkbox"/> Failed to Strike	The lamp failed to strike.
		<input checked="" type="checkbox"/> Lamp Off - Unknown	The lamp was on but extinguished unexpectedly.
		<input checked="" type="checkbox"/> Lamp Off - Interlock	The lamp was on but turned off due to a tripped interlock.
		<input checked="" type="checkbox"/> Lamp Off - Fan Failure	The lamp was on but turned off due to a bulb blower or reflector fan failure.
61	Lamp B1 Hours	<input type="checkbox"/> <hours> : <minutes> (h:m)	The total amount of time that the lamp has been on.
		<input type="checkbox"/> Unknown	The lamp hours are unknown because the lamp memory module cannot be communicated with. See the Lamp B1 Memory Module status item for details of the failure.
		<input checked="" type="checkbox"/> <hours> : <minutes> (h:m) - Lamp is past expiry	The lamp is running past its maximum number of hours.
63	Lamp B1 Installation Date	<input type="checkbox"/> <YYYY>/<MM>/<DD>	Displays the date the lamp was installed.
		<input type="checkbox"/> Unknown	The lamp installation date is unknown because the lamp memory module cannot be communicated with. See the Lamp B1 Memory Module status item for details of the failure.
64	Lamp B1 S/N	<input type="checkbox"/> <value>	Displays the serial number of the installed lamp.
		<input type="checkbox"/> Unknown	The lamp serial number is unknown because the lamp memory module cannot be communicated with. See the Lamp B1 Memory Module status item for details of the failure.

#	Status	Sta Value	Description	
66	Lamp B1 Voltage	<input type="text" value=""/>	<voltage>V	Displays the voltage being applied to the lamp as reported by the lamp driver.
		<input type="text" value=""/>	Unknown	The lamp state is unknown because the lamp driver could not be communicated with. See the Lamp B1 Memory Module status item for details of the failure.
70	Lamp B2 State	<input type="text" value=""/>	On	The lamp is on.
		<input type="text" value=""/>	Warming Up	The lamp is warming up.
		<input type="text" value=""/>	Off	The lamp is off.
		<input type="text" value=""/>	Cooling Down	The lamp is cooling down.
		<input type="text" value=""/>	Waiting to Strike	The lamp is cooling down but will turn on as soon as the cool down is complete.
		<input type="text" value=""/>	Failed to Strike	The lamp failed to strike.
		<input type="text" value=""/>	Lamp Off - Unknown	The lamp was on but extinguished unexpectedly.
		<input type="text" value=""/>	Lamp Off - Interlock	The lamp was on but turned off due to a tripped interlock.
		<input type="text" value=""/>	Lamp Off - Fan Failure	The lamp was on but turned off due to a bulb blower or reflector fan failure.
71	Lamp B2 Hours	<input type="text" value=""/>	<hours>:<minutes> (h:m)	The total amount of time that the lamp has been on.
		<input type="text" value=""/>	Unknown	The lamp hours are unknown because the lamp memory module cannot be communicated with. See the Lamp B2 Memory Module status item for details of the failure.
		<input type="text" value=""/>	<hours>:<minutes> (h:m) - Lamp is past expiry	The lamp is running past its maximum number of hours.
73	Lamp B2 Installation Date	<input type="text" value=""/>	<YYYY>/<MM>/<DD>	Displays the date the lamp was installed.
		<input type="text" value=""/>	Unknown	The lamp installation date is unknown because the lamp memory module cannot be communicated with. See the Lamp B2 Memory Module status item for details of the failure.

#	Status	Sta Value te	Description	
74	Lamp B2 S/N	<input type="text"/>	<value>	Displays the serial number of the installed lamp.
		<input type="text"/>	Unknown	The lamp serial number is unknown because the lamp memory module cannot be communicated with. See the Lamp B2 Memory Module status item for details of the failure.
76	Lamp B2 Voltage	<input type="text"/>	<voltage>V	Displays the voltage being applied to the lamp as reported by the lamp driver.
		<input type="text"/>	Unknown	The lamp state is unknown because the lamp driver could not be communicated with. See the Lamp B2 Memory Module status item for details of the failure.
80	Lamp B3 State	<input type="text"/>	On	The lamp is on.
		<input type="text"/>	Warming Up	The lamp is warming up.
		<input type="text"/>	Off	The lamp is off.
		<input type="text"/>	Cooling Down	The lamp is cooling down.
		<input type="text"/>	Waiting to Strike	The lamp is cooling down but will turn on as soon as the cool down is complete.
		<input type="checkbox"/>	Failed to Strike	The lamp failed to strike.
		<input type="checkbox"/>	Lamp Off - Unknown	The lamp was on but extinguished unexpectedly.
		<input type="checkbox"/>	Lamp Off - Interlock	The lamp was on but turned off due to a tripped interlock.
81	Lamp B3 Hours	<input type="text"/>	<hours>:<minutes> (h:m)	The total amount of time that the lamp has been on.
		<input type="text"/>	Unknown	The lamp hours are unknown because the lamp memory module cannot be communicated with. See the Lamp B3 Memory Module status item for details of the failure.
		<input type="checkbox"/>	<hours>:<minutes> (h:m) - Lamp is past expiry	The lamp is running past its maximum number of hours.
		<input type="checkbox"/>		

#	Status	State	Value	Description
83	Lamp B3 Installation Date	<input type="checkbox"/>	<YYYY>/<MM>/<DD>	Displays the date the lamp was installed.
		<input type="checkbox"/>	Unknown	The lamp installation date is unknown because the lamp memory module cannot be communicated with. See the Lamp B3 Memory Module status item for details of the failure.
84	Lamp B3 S/N	<input type="checkbox"/>	<value>	Displays the serial number of the installed lamp.
		<input type="checkbox"/>	Unknown	The lamp serial number is unknown because the lamp memory module cannot be communicated with. See the Lamp B3 Memory Module status item for details of the failure.
86	Lamp B3 Voltage	<input type="checkbox"/>	<voltage>V	Displays the voltage being applied to the lamp as reported by the lamp driver.
		<input type="checkbox"/>	Unknown	The lamp state is unknown because the lamp driver could not be communicated with. See the Lamp B3 Memory Module status item for details of the failure.

Version Group (SST+VERS?)

The Version Group provides values and fault conditions related to software and hardware versions for Boxer 4K.



Some of the lamp driver statuses listed below may not be applicable for your installation as the model of projector determines the number of lamps in the projector.

#	Status	State	Value	Description
0	Main Control Board SW Version	<input type="checkbox"/>	<version>	Displays the software version running on the controller board.
		<input type="checkbox"/>	Unknown	Cannot determine the software version information.
1	Main Control Board HW Version	<input type="checkbox"/>	<name>.<level>.<mod>	<name> = Short name of the board <level> = Version of the board <mod> = Modification level of the board
		<input type="checkbox"/>	Detection Fault	Cannot read the board type information.

#	Status	State	Value	Description
2	Backplane HW Version	<input type="checkbox"/>	<name>.<level>.<mod>	<p><name> = Short name of the board <level> = Version of the board <mod> = Modification level of the board</p> <p>This information is cached while the projector is in standby.</p>
		<input type="checkbox"/>	N/A	The backplane has never been turned on or initialized.
3	Image Processor HW Version	<input type="checkbox"/>	<name>.<level>.<mod>	<p><name> = Short name of the board <level> = Version of the board <mod> = Modification level of the board</p> <p>This information is cached while the projector is in standby.</p>
		<input type="checkbox"/>	N/A	The image processor board has never been turned on or initialized.
4 5 6	Formatter-Red HW Version Formatter-Green HW Version Formatter-Blue HW Version	<input type="checkbox"/>	<name>.<level>.<mod>	<p><name> = Short name of the board <level> = Version of the board <mod> = Modification level of the board</p> <p>This information is cached while the projector is in standby.</p>
		<input type="checkbox"/>	N/A	The formatter failed to be detected or initialized.
7 8 9 10	Option Card 1 HW Version Option Card 2 HW Version Option Card 3 HW Version Option Card 4 HW Version	<input type="checkbox"/>	<name>.<level>.<mod>	<p><name> = Short name of the board <level> = Version of the board <mod> = Modification level of the board</p> <p>This is cached information while the projector is in standby.</p>
		<input type="checkbox"/>	N/A	The option card has never been turned on or initialized.
17	Power Supply HW Version	<input type="checkbox"/>	<hardware version>.<boot version>.<main version>	<p><hardware version> = Hardware version of power supply <boot version> = Version of power supply bootloader <main version> = Version of power supply main firmware</p>
		<input type="checkbox"/>	Unknown	Cannot retrieve the hardware version.

#	Status	State	Value	Description
18	Housekeeping Board HW Version	<input type="checkbox"/>	<name>.<level>.<mod>	<name> = Name of the board (such as HKBA) <level> = Hardware version of the board <mod> = Modification level of the board
		<input type="checkbox"/>	Unknown	Cannot retrieve the hardware version.
19	Keypad Display HW Version	<input type="checkbox"/>	<name>.<level>.<mod>	<name> = Name of the board (such as IKB) <level> = Hardware version of the board <mod> = Modification level of the board
		<input type="checkbox"/>	Unknown	Cannot retrieve the hardware version as the board is not ready.
20	Lamp A1 Driver HW Version	<input type="checkbox"/>	<version>	Displays lamp driver information.
21	Lamp A2 Driver HW Version	<input type="checkbox"/>		
22	Lamp A3 Driver HW Version	<input type="checkbox"/>	Unknown	Cannot retrieve the hardware version of the lamp driver.
23	Lamp B1 Driver HW Version	<input type="checkbox"/>		
24	Lamp B2 Driver HW Version	<input type="checkbox"/>		
25	Lamp B3 Driver HW Version	<input type="checkbox"/>		
34	Option Card 0 HW Version	<input type="checkbox"/>	<name>.<level>.<mod>	<name> = Short name of the board <level> = Version of the board <mod> = Modification level of the board This information is cached while the projector is in standby.
		<input type="checkbox"/>	N/A	The option card has never been turned on or initialized.






















Temperature Group (SST+TEMP?)

























The Temperature Group provides values and fault conditions for temperature-related items in Boxer 4K.



















Some of the lamp driver statuses listed below may not be applicable for your installation as the model of projector determines the number of lamps in the projector.

#	Status	State	Value	Description
2	Air Intake Temperature (Temp 2)	<input type="checkbox"/>	<value> °C	Displays the current temperature of the sensor.

#	Status	State	Value	Description
			Unknown	Temperature reading is unavailable.
			Communication Fault (shutdown)	Cannot retrieve the temperature from sensor.
			<value> °C - High Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Hot (shutdown)	Temperature is exceeding the error threshold.
			<value> °C - Low Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Cold (shutdown)	Temperature is below the error threshold.
4	Main Control Board Temperature		<value> °C	Displays the current temperature of the sensor.
5	Backplane Temperature		N/A	Temperature reading is unavailable.
6	Image Processor Scaler Temperature			
7	Image Processor Warp-Red Temperature		Communication Fault (shutdown)	Cannot retrieve the temperature from sensor.
8	Image Processor Warp-Green Temperature			
9	Image Processor Warp-Blue Temperature			
10	Formatter-Red Temperature		<value> °C - High Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Hot (shutdown)	Temperature is exceeding the error threshold.
			<value> °C - Low Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Cold (shutdown)	Temperature is below the error threshold.
11	DMD Waterblock Temperature		<value> °C	Displays the current temperature of the sensor.
			Unknown	Temperature reading is unavailable.
			Not Present	The temperature sensor is not present.
			Communication Fault (shutdown)	Cannot retrieve the temperature from sensor.
			<value> °C - High Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Hot (shutdown)	Temperature is exceeding the error threshold.
			<value> °C - Low Temperature	Temperature is sitting inside the warning band.

#	Status	State	Value	Description
			<value> °C - Too Cold (shutdown)	Temperature is below the error threshold.
12	Formatter-Green Temperature		<value> °C	Displays the current temperature of the sensor.
14	Formatter-Blue Temperature		N/A	Temperature reading is unavailable.
16	Option Card 1 Temperature		N/A	Temperature reading is unavailable.
17	Option Card 2 Temperature		N/A	Temperature reading is unavailable.
18	Option Card 3 Temperature		Communication Fault (shutdown)	Cannot retrieve the temperature from sensor.
19	Option Card 4 Temperature		Communication Fault (shutdown)	Cannot retrieve the temperature from sensor.
			<value> °C - High Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Hot (shutdown)	Temperature is exceeding the error threshold.
			<value> °C - Low Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Cold (shutdown)	Temperature is below the error threshold.
20	Housekeeping Board Temperature		<value> °C	Displays the current temperature of the sensor.
23	Lamp A1 Driver Temperature		<value> °C	Displays the current temperature of the sensor.
24	Lamp A2 Driver Temperature		Unknown	Temperature reading is unavailable.
25	Lamp A3 Driver Temperature		Unknown	Temperature reading is unavailable.
26	Lamp B1 Driver Temperature		Communication Fault (shutdown)	Cannot retrieve the temperature from sensor.
27	Lamp B2 Driver Temperature		Communication Fault (shutdown)	Cannot retrieve the temperature from sensor.
28	Lamp B3 Driver Temperature		Communication Fault (shutdown)	Cannot retrieve the temperature from sensor.
			<value> °C - High Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Hot (shutdown)	Temperature is exceeding the error threshold.
			<value> °C - Low Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Cold (shutdown)	Temperature is below the error threshold.
29	Main Control Board FPGA Temperature		<value> °C	Displays the current temperature of the sensor.
			N/A	Temperature reading is unavailable.
			Communication Fault (shutdown)	Cannot retrieve the temperature from sensor.
			<value> °C - High Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Hot (shutdown)	Temperature is exceeding the error threshold.


























#	Status	State	Value	Description
			<value> °C - Low Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Cold (shutdown)	Temperature is below the error threshold.
34 35 36	Power Supply Heat Sink 3 Temperature Power Supply Heat Sink 5 Temperature		<value> °C Power Supply Heat Sink 2 Temperature	Displays the current temperature of the sensor.
			Unknown	Temperature reading is unavailable.
			Communication Fault (shutdown)	Cannot retrieve the temperature from sensor.
			<value> °C - High Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Hot (shutdown)	Temperature is exceeding the error threshold.
			<value> °C - Low Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Cold (shutdown)	Temperature is below the error threshold.
37	Option Card 0 Temperature		<value> °C	Displays the current temperature of the sensor.
			N/A	Temperature reading is unavailable.
			Communication Fault (shutdown)	Cannot retrieve the temperature from sensor.
			<value> °C - High Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Hot (shutdown)	Temperature is exceeding the error threshold.
			<value> °C - Low Temperature	Temperature is sitting inside the warning band.
			<value> °C - Too Cold (shutdown)	Temperature is below the error threshold.





Cooling Group (SST+COOL?)

The Cooling Group provides values and fault conditions related to cooling and fans for Boxer 4K.








Some of the lamp and bulb blower statuses listed below may not be applicable for your installation as the model of projector determines the number of lamps in the projector.














#	Status	State	Value	Description
0	Intake A (Fan 19)		<tach> RPM	Displays the current tachometer reading.
1	Intake B (Fan 20)			
3	Formatter-Green (Fan 23)		Off	Fan is off.
4	LAD Blower A (Fan 26)			
5	Card Cage Intake (Fan 32)		Unknown	The tachometer reading is unavailable.
6	Card Cage Intake (Fan 33)			
8	HIP Blower A (Fan 17)		<tach> RPM - Low RPM	Fan tachometer reading is lower than the minimum recommended speed.
9	Card Cage Exhaust (Fan 30)		Off - Overridden	Fan is off. The fan speed has been changed from its default recommended value.
10	Card Cage Exhaust (Fan 31)		<tach> RPM - Overridden	Fan is on. The fan speed has been changed from its default recommended value.
12	Liquid Cooling Flow Meter		<value> L/min	Displays the amount of liquid flowing past the sensor.
			Off	Liquid cooling is off.
			Unknown	The tachometer reading is unavailable.
			<value> L/min - Flow Impeded	The flow reading is lower than the minimum recommended threshold.
13	Liquid Cooling Pump		<tach> RPM	Displays the current tachometer reading.
			Off	Fan is off.
			Unknown	The tachometer reading is unavailable.
			<tach> RPM - Low RPM	Fan tachometer reading is lower than the minimum recommended speed.
15	HIP Blower B (Fan 18)		<tach> RPM	Displays the current tachometer reading.
16	Lamp Driver Exhaust (Fan 22)			
17	Lamp Driver Intake (Fan 21)		Off	Fan is off.
18	Bulb Blower A1 (Fan 6)			
19	Bulb Blower A2 (Fan 5)		Unknown	The tachometer reading is unavailable.
20	Bulb Blower A3 (Fan 4)			
21	Bulb Blower B1 (Fan 3)		<tach> RPM - Low RPM	Fan tachometer reading is lower than the minimum recommended speed.
22	Bulb Blower B2 (Fan 2)			
23	Bulb Blower B3 (Fan 1)			

#	Status	State	Value	Description
24	Lamp Fan A1 (Fan 12)		Off - Overridden	Fan is off. The fan speed has been changed from its default recommended value.
25	Lamp Fan A2 (Fan 10)			
26	Lamp Fan A3 (Fan 8)			Fan is on. The fan speed has been changed from its default recommended value.
27	Lamp Fan B1 (Fan 11)		<tach> RPM - Overridden	
28	Lamp Fan B2 (Fan 9)			
29	Lamp Fan B3 (Fan 7)			
31	Formatter-Red (Fan 24)			
33	Radiator Fan A (Fan 13)			
34	Radiator Fan B (Fan 14)			
35	Radiator Fan C (Fan 15)			
36	Radiator Fan D (Fan 16)			
37	LAD Blower B (Fan 27)			
43	Formatter-Blue (Fan 25)			
	Lamp Door Fan 1 (Fan 28)			
	Lamp Door Fan 2 (Fan 29)			
45	Power Supply Fan 1		<tach> RPM	Displays the current tachometer reading.
46	Power Supply Fan 2			The status of this output is unknown because the power supply cannot be communicated with.
47	Power Supply Fan 3		Unknown	

Serial Group (SST+SERI?)

The Serial Group provides values and fault conditions related to hardware serial numbers for Boxer 4K.

#	Status	State	Value	Description
0	Main Control Board S/N		<serial number>	Displays the electronic serial number of the main control board.
			Missing S/N	Cannot retrieve the value because the serial number was not programmed into the board correctly.
1	Backplane S/N		<serial number>	Displays the electronic serial number of the backplane.
			N/A	The information is not currently available (card not present or not powered).
			Missing S/N	Cannot retrieve the value because the serial number was not programmed into the board correctly

#	Status	State	Value	Description	
2	Image Processor S/N		<serial number>	Displays the electronic serial number of the board.	
			N/A	The information is not currently available (card not present or not powered).	
			Missing S/N	Cannot retrieve the value because the serial number was not programmed into the board correctly	
3	Formatter-Red S/N		<serial number>	Displays the electronic serial number of the formatter.	
4	Formatter-Green S/N		N/A	The information is not currently available (card not present or not powered).	
5	Formatter-Blue S/N		Missing S/N	Cannot retrieve the value because the serial number was not programmed into the board correctly	
6	Option Card 1 S/N		<serial number>	Displays the electronic serial number of the option card.	
7	Option Card 2 S/N		N/A	The information is not currently available (card not present or not powered).	
8	Option Card 3 S/N			Missing S/N	Cannot retrieve the value because the serial number was not programmed into the board correctly
9	Option Card 4 S/N				
14	Housekeeping Board S/N		<serial number>	Displays the electronic serial number of the board.	
15	Keypad Display S/N			Unknown	The serial number is unavailable because the board is not ready.
				Missing Serial Number	Cannot retrieve the value because the serial number was not programmed into the board correctly.
16	Option Card 0 S/N		<serial number>	Displays the electronic serial number of the option card.	
			N/A	The information is not currently available (card not present or not powered).	
			Missing S/N	Cannot retrieve the value because the serial number was not programmed into the board correctly	

Corporate offices

Christie Digital Systems USA, Inc.
ph: 714 236 8610

Christie Digital Systems Canada Inc.
ph: 519 744 8005

Worldwide offices

Africa
ph: +27 (0)11 510 0094

Australia
ph: +61 (0) 7 3624 4888

Brazil
ph: +55 (11) 2548 4753

China (Beijing)
ph: +86 10 6561 0240

China (Shanghai)
ph: +86 21 6030 0500

Columbia
ph: +57 (318) 447 3179

France
ph: +33 (0) 1 41 21 44 04

Germany
ph: +49 2161 566200

India
ph: +91 (080) 6708 9999

Japan (Tokyo)
ph: 81 3 3599 7481

Korea (Seoul)
ph: +82 2 702 1601

Mexico
ph: +52 55 4744 1790

Singapore
ph: +65 6877 8737

Spain
ph: +34 91 633 9990

Middle East
ph: +971 (0) 503 6800

United Kingdom
ph: +44 (0) 118 977 8000

United States (Arizona)
ph: 602 943 5700

Independent sales consultant offices

Italy
ph: +39 (0) 2 9902 1161

Russia
ph: +36 (0) 1 47 48 100



For the most current technical documentation, visit www.christiedigital.com.

