Christie LWU620i lens throw ratios

The following table details the information required to calculate the lens throw ratios for the Christie LWU620i projectors.

Lens	Throw distance formula		Vertical and horizontal	Diagonal screen sizes	
	Imperial (in)	Metric (cm)	offset (%)	Imperial (in)	Metric (cm)
0.8:1 fixed (121-111104-XX)	TD = 0.80 x W + 3.56	TD = 0.80 x W + 9.04	0% V	30 to 600	76 to 1524
			0% H		
1.2 - 1.7:1 short zoom (121-129103-XX)	TDmin = 1.17 x W + 2.90	TDmin = 1.17 x W + 7.38	0% - 50% V	30 to 600	76 to 1524
	$TDmax = 1.76 \times W + 2.85$	$TDmax = 1.76 \times W + 7.25$	±10% H		
1.7 - 2.9:1 medium zoom (121-130105-XX)	TDmin = 1.71 x W + 3.36	TDmin = 1.71 x W + 8.54	0% - 55% V	30 to 600	76 to 1524
	$TDmax = 2.90 \times W + 3.17$	$TDmax = 2.90 \times W + 8.05$	±10% H		
2.8 - 4.8:1 long zoom (121-114107-XX)	TDmin = 2.82 x W + 2.31	TDmin = 2.82 x W + 5.87	0% - 50% V	30 to 600	76 to 1524
	TDmax = 4.83 x W - 0.48	TDmax = 4.83 x W - 1.22	±10% H		
4.7 - 8.1:1 ultra long zoom (121-115108-XX)	TDmin = 4.67 x W + 12.46	TDmin = 4.67 x W + 31.65	0% - 50% V	30 to 600	76 to 1524
	$TDmax = 8.05 \times W + 10.72$	$TDmax = 8.05 \times W + 27.22$	±10% H		

- Throw distance measured from the center of the front foot of the projector.
- All lenses are made of glass.
- $\label{eq:continuity} \textbf{i} \cdots \textbf{7} \textbf{U} \cdot \textbf{W} \cdot \textbf{U} + \textbf{X} \cdot \textbf{h} \cdot \textbf{fck} \cdot \textbf{X} \\ \textbf{2} \textbf{g} + \textbf{U} \cdot \textbf{b} \cdot \textbf{W} \cdot \textbf{f} + \textbf{B} \cdot \textbf{E} \cdot \textbf{j} \cdot \textbf{U} \cdot \textbf{i} \cdot \textbf{Y} \cdot \textbf{g} \cdot \textbf{j} \cdot \textbf{U} \cdot \textbf{i} \cdot \textbf{Z} \\ \textbf{2} \textbf{g} \cdot \textbf{J} \cdot \textbf{$