

Christie FHQ842-T

Affordable, interactive 84" LCD display with 24/7 capabilities


Technical specifications		Christie FHQ842-T
Display technology	screen size (diagonal)	• 84"
	native resolution	• 3840 x 2160 (16:9)
	backlight	• Edge-lit LED
	LED lifespan	• 30,000 hrs (50% brightness)
	display orientation	• Landscape
	pixel pitch	• 0.4845 x 0.4845mm
	nominal bezel size	• 35mm
	brightness	• 320 nits (cd/m ²) typical
	contrast ratio (full field)	• 750:1
	viewing angle (CR 10:1)	• 178° h/v
	refresh rate	• 120Hz
	response time	• 8ms
	color space (CIE 1931)	• 72%
display colors	• 10 bit • 1.06 billion	
Signal	inputs	• HDMI 1.4b x 4 • DisplayPort 1.2 • VGA • USB type A (firmware updates) • USB 2.0 type B (Touch control) • IR • OPS-HDMI 1.4b • OPS-DP 1.1a • AC • Infrared Receiver • Audio 3.5mm • 6 key control buttons
	outputs	• Audio 3.5mm
Control	inputs	• RS-232 via extension cable (included)
Power	input rating	• 100-240 VAC @ 50/60Hz
	power consumption	• Without OPS: 500W maximum; 315 typical • With OPS: 620W maximum; 330 typical • >=0.5W standby
Environment	operating temperature	• 32-104°F (0-40°C)
	operating humidity	• 20-80% RH non-condensing
	storage temperature	• 4-140°F (-20-60°C)
Physical	size	• (WxHxD): 77.80 x 45.71 x 4.11" (1976 x 1161 x 104.5mm) • (D): 3.81" (96.7mm) without handle
	weight	• 211.6lbs (96kg)
	panel mount locations	• VESA standard (WxH) 600 x 600mm
Runtime	• Designed for 24/7 operation featuring a reliable power supply and cooling system ¹	
Features	• Commercial-grade LCD • Anti-glare coating • UHD resolution (3840 x 2160 @120Hz) • Landscape only • 10 point multi-touch ²	
	• Plug and Play (DDC2B) • Motion Estimation Motion Compensation (MEMC) supported	
	• Multi-window options including: Dual, Quad (allowable resolution: ≤ 1080p @ 60Hz)	
	• Sleep mode • Control with on screen display (OSD) using infrared (IR) remote control • Built in 10W x 2 speakers	
Accessories	• Panel ships with remote control • External IR receiver • RS-232 cable • USB cable • Quick start guide and multi-language user manual CD	
Warranty	• Three years parts and labor limited warranty • Contact an authorized Christie representative for full details of our limited warranty	

¹ Avoid static images for extended periods. Refer to the user manual for additional runtime guidelines.


² Requires Windows 7 Home Premium or higher. MacOS or Linux requires drivers, and supports single touch only.

Content and operating conditions can affect the useful life of the product. Please refer to the product user manual and Christie Operating Guidelines for Flat Panels, available at www.christieemea.com.


Right side view



Front view



Back view



Other EMEA offices

United Kingdom
Branch & EMEA
Head Office
ViewPoint
200 Ashville Way
Wokingham
Berkshire, U.K.
RG41 2PL
PH: +44 (0) 118 977 8000

Middle East
Light Industrial Unit (LIU-17)
Nad Al Shibba
Sheikh Mohammed Bin Zayed Road
Dubai Silicon Oasis
PO Box: 293762
Dubai - U.A.E
PH: +971 (0) 4 503 6800

Africa
Unit C3
Northlands Deco Park
New Market Road
Northriding
Randburg
2164
Johannesburg
Gauteng
South Africa
PH: +27 71 335 8667

Germany
Branch Office
PH: +49 2161 566 200

France
Branch Office
PH: +33 (0) 1 41 21 44 04

Eastern Europe
Representative Office
PH: +36 (0)1 47 48 138

Spain
Branch Office
PH: +34 91 633 9990

Italy
Independent Sales Consultant Office
PH: +39 (0) 2 9902 1161

Russia
Independent Sales Consultant Office
PH: +7 (495) 930-8961

For the most current specification information, please visit www.christieemea.com



Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4111 Aug 15

CHRISTIE®