

# Christie Boxer 2K20 and 2K30

		Christie Boxer 2K20 144-007108-01	Christie Boxer 2K30 144-009100-01
Image	brightness	<ul style="list-style-type: none"> <li>• 19,500 ANSI (typical)</li> <li>• 20,000 Center</li> <li>• 22,000 ISO</li> </ul>	<ul style="list-style-type: none"> <li>• 29,000 ANSI (typical)</li> <li>• 30,000 Center</li> <li>• 32,500 ISO</li> </ul>
	contrast	• 2000:1	
Display technology	type	<ul style="list-style-type: none"> <li>• 3DLP® 1.38" DMD</li> <li>• 4K (4096 x 2160)</li> </ul>	
	resolution limit	• 2K (2048 x 1080)	
Lamp	type	• 4 x 450W NSH	• 6 x 450W NSH
	life	• 1500 hrs to 70% initial brightness, and up to 2500 at 50%	
Inputs	<ul style="list-style-type: none"> <li>• High bandwidth multi-input card (HBMIC)</li> <li>• HDBaseT</li> </ul>		
Pixel clock	• 300 Mpx/s - Christie® TruLife Lite Electronics		
Networking	<ul style="list-style-type: none"> <li>• Keypad</li> <li>• RS232 in</li> <li>• Ethernet (10/100) RJ45</li> </ul>		
Lens mount	<ul style="list-style-type: none"> <li>• Tool-free lens insertion system</li> <li>• Boresight adjustable</li> <li>• Motorized horizontal and vertical lens offset</li> <li>• Motorized zoom and focus adjustment</li> </ul>		
Lenses	fixed	<ul style="list-style-type: none"> <li>• 0.72:1 (no offset)</li> <li>• 0.9:1 (offset: V: ±45%, H: ±15%)</li> </ul>	
	zoom	<ul style="list-style-type: none"> <li>• 1.13-1.31:1 (offset: V: ±60%, H: 25%)</li> <li>• 1.31-1.63:1 (offset: V: ±80%, H: 30%)</li> <li>• 1.63-2.17:1 (offset: V: ±80%, H: 30%)</li> <li>• 1.99-2.71:1 (offset: V: ±15%, H: 5%)</li> <li>• 2.71-3.89:1 (offset: V: ±45%, H: 15%)</li> <li>• 3.89-5.43:1 (offset: V: ±85%, H: 25%)</li> <li>• 4.96-1-7.69:1 (offset: V: ±55%, H: 20%)</li> </ul>	
Optional accessories	<ul style="list-style-type: none"> <li>• Dual link DVI input card</li> <li>• Twin HDMI™ input card</li> <li>• Dual 3G HD-SDI input card</li> <li>• Twin DisplayPort input card</li> <li>• Quad DisplayPort input card</li> <li>• Christie Link Transmitter (Fiber)</li> <li>• Rigging and stacking frame</li> <li>• High bandwidth multi-input card (HBMIC)</li> </ul>		
Power requirements	operating voltage	• 200-240V	
	operating current	• 19A	
Dimensions	size	• (LxWxH): 37.75 x 23.5 x 12" (959 x 597 x 305mm)	
	weight	• 160lbs (72.57kg)	
Operating environment	temperature	• 41-104°F (5-40°C)	
	humidity	• 10-80%, non-condensing	
Warranty	• Three years		

For Christie Boxer 4K20 and 4K30 specs, please visit [christiedigital.com](http://christiedigital.com).

United Kingdom  
Branch & EMEA  
Head Office  
ViewPoint  
200 Ashville Way  
Wokingham  
Berkshire, U.K.  
RG41 2PL  
PH: +44 (0) 118 977 8000

Middle East  
Light Industrial Unit (LIU-17)  
Nad Al Shibba  
Sheikh Mohammed Bin Zayed Road  
Dubai Silicon Oasis  
PO Box: 293762  
Dubai - U.A.E  
PH: +971 (0) 4 503 6800

Africa  
Unit C3  
Northlands Deco Park  
New Market Road  
Northriding  
Randburg  
2164  
Johannesburg  
Gauteng  
South Africa  
PH: +27 11 251 0000

## Other EMEA offices

Germany  
Branch Office  
PH: +49 2161 566 200

France  
Branch Office  
PH: +33 (0) 1 41 21 44 04

Spain  
Branch Office  
PH: +34 91 633 9990

Italy  
Independent Sales Consultant Office  
PH: +39 (0) 2 9902 1161

Russia  
Independent Sales Consultant Office  
PH: +7 (495) 930-8961



For the most current specification information, please visit [www.christieemea.com](http://www.christieemea.com)

Copyright 2017 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4480 Mar 17

**CHRISTIE®**