

# CHRISTIE CDA2

Mainstream cinema | Immersive auditoriums | Post production | Premium large format

Exceptionally powerful and efficient Class D amplification  
for distortion-free signal reproduction



**CHRISTIE**  
VIVE AUDIO

## CLASS D AMPLIFICATION

Cinema's first highly efficient  
and reliable amplifier

### Key features:

- › **Versatile and reliable** – Designed for long-term continuous operation for a range of applications
- › **Easy to diagnose** – Active, signal present, DC protection, and thermal LED indicators
- › **Multi-mode functionality** – parallel/bridge/stereo mode switch with high current switch mode power supply
- › **Perfect match** – high current capability and fast transient response makes it ideal for all loudspeakers
- › **Powerfully efficient output** – high-power, low-heat, high stability even with low impedance loads



## Specifications

## Christie CDA2

Rated power	bridge 4 ohms	• 1960W @ 1kHz 1% T.H.D.
	bridge 8 ohms	• 1160W @ 1kHz 1% T.H.D.
	2 x 2 ohms	• 980W per channel @ 1kHz 1% T.H.D. both channels driven
	2 x 4 ohms	• 540W per channel @ 1kHz at <0.1% T.H.D. both channels driven
	2 x 8 ohms	• 275W per channel @ 1kHz at <0.1% T.H.D. both channels driven
	1 x 2 ohms	• 1050W @ 1kHz at <0.1% T.H.D.
	1 x 4 ohms	• 600W @ 1kHz at <0.1% T.H.D.
	1 x 8 ohms	• 290W @ 1kHz at <0.1% T.H.D.
Minimum load impedance	• 2 ohms	
Maximum RMS voltage swing	• 56V	
Frequency response	• 10Hz-45kHz; 0dB, -3dB @ 1W	
T.H.D.	2 x 2 ohms	• <0.1% @ 800W per channel from 20Hz-10kHz, decreasing to 760W @ 20kHz
	2 x 4 ohms	• <0.1% @ 500W per channel from 20Hz-20kHz
	2 x 8 ohms	• <0.1% @ 270W per channel from 20Hz-20kHz
Input CMRR	• >-77dB @ 1kHz	
Voltage gain	• x60 (+35dB)	
Crossover	• 100Hz switchable 2nd order high pass and 3rd order low pass per channel	
Crosstalk	• >-70dB @ 1kHz at 100W power @ 4 ohms	
Hum and noise	• >-100dB, "A" weighted referenced to rated power @ 4 ohms	
Slew rate	• >12V/μs	
Damping factor (8 ohms)	• >250:1 @ 20Hz-1kHz @ 8 ohms	
Phase response	• +6 to -70° from 20Hz-20kHz	
Input sensitivity	• 0.775V ±3% for 1kHz 4 ohm rated power • 0.735V ± 3% for 1kHz 2 ohm rated power	
Input impedance	• 15k ohms balanced • 7.5k ohms unbalanced	
Current draw	@ 1/8 power	• 620W @ 2 ohms • 390W @ 4 ohms • 250W @ 8 ohms
	@ 1/3 power	• 1250W @ 2 ohms • 810W @ 4 ohms • 460W @ 8 ohms
Cooling	• Temperature dependent variable speed 80mm DC fan	
Controls	• T2 front panel attenuators • Crossover select switch for H.P.F, Normal and L.P.F • Input mode switch for Stereo, Bridge and Parallel	
Indicator LEDs	• 2 DDT (ACL clip limiting) • 2 signal presence • 2 active status • 2 temp • 2 DC protect	
Protection	• Thermal • DC • Subsonic • Incorrect loads • Under and over voltage	
Connectors	inputs	• Neutrik Dual Combi 1/4" XLR
	outputs	• Three Neutrik Speakon connectors for two channels plus common bridge
Construction	• 18 ga. galvanized steel	
Dimensions	• (LxWxH) 10.5 x 19 x 3.5" (266 x 482 x 89mm) behind front panel + 0.6" for handle • 2 RU mounting	
Net weight	• 10.90lbs (4.94kg) <sup>1</sup>	
Gross weight	• 13.3lbs (6.02kg)	
Warranty	• Limited 5-year warranty	

Rated power readings made with BW: <10Hz-22kHz. All power measurements made at 120 VAC. 2 ohm power is time limited by circuit breaker. Input power requirements: 120 VAC, 60Hz, 5A.

<sup>1</sup> Net weight does not include power cord.

### Corporate offices

### Worldwide offices

Christie Digital Systems USA, Inc. Cypress PH: +1 714-236-8610	Australia PH: +61 (0) 7 3624 4888	China (Shenzhen) PH: + 86 755 3680 7000	Mexico PH: +52 (55) 4744-1791	United Arab Emirates PH: +971 (0) 4 503 6800
Christie Digital Systems Canada Inc. Kitchener PH: +1 519-744-8005	Brazil PH: +55 11 3181-2952	Colombia PH: +57 (315) 652-9620	Singapore PH: +65 6877 8737	United Kingdom PH: +44 (0) 118 977 8000
	China (Beijing) PH: +86 10 6561 0240	Germany PH: +49 221 99 512-0	South Korea PH: +82 2 702 1601	United States (Arizona) PH: +1 602-943-5700
	China (Shanghai) PH: +86 21 6030 0500	India PH: +91 (080) 6708 9999	Spain PH: +34 (0) 91 633 99 90	United States (Texas) PH: +1 469-757-4420

For the most current specification information, please visit [christiedigital.com](http://christiedigital.com)

Copyright 2023 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.  
CD4177-CDA2-Datasheet-Jan-24-EN-US

