

CINELIFE+™ SERIES

From boutique cinemas to Premium Large-Format (PLF) auditoriums

Bring stories to life with bright, colorful visuals from the world's most advanced cinema projection



Key features:

- › **Quick and easy setup** - The auto-configure feature automatically adjusts settings for optimal playback when you connect different sources
- › **Advanced format cinema** - High Frame Rate (HFR) support for 2K and 4K 2D content at 120fps and 60fps/per eye for 3D content
- › **Remote UI** - Use a web browser to access the interface anywhere
- › **Hyperrealism** - New system architecture displays content without motion blur or artifacts
- › **Ultra-fast processing** - HDMI 2.0 and 4 x 12GB SDI inputs for 1.06G pixels per second
- › **Electronic Color Convergence (ECC)** - Provides perfect alignment throughout the entire image
- › **Long-lasting light source** - More than 50,000 hours of optimal performance for RGB pure laser models



CHRISTIE PHAZER

Enhanced laser light source designed for incredible visuals on all cinema screens.

CHRISTIE RealLaser

Advanced laser light source for accurate reproduction of DCI content

CineLife+™

Advanced format cinema with HFR support including 4K 120fps native 3D playback

CINEMA CALCULATOR

Find the right projector and lens for your screen

CP4455-RGB



Premium large format auditoriums |
Advanced format cinema | Event cinema

CP4445-RGB



Premium large format auditoriums |
Advanced format cinema | Event cinema

CP4435-RGB



Large-screen auditoriums | Event cinema |
Post production

CP4425-RGB



Large-screen auditoriums | Event cinema |
Post production

Operational efficiency: 11.3 lumens per watt

Specifications: Up to 6,000:1 contrast | >95% of Rec. 2020 color gamut | Up to 57,000 lumens with HB lens, 42,000 lumens with UHC lens

Power consumption: 5,037 W including chiller, max DCI brightness, at 25 C 17,299 BTU/hr

Dimensions: 61.1 x 28.0 x 22.0"
(1551.1 x 710.6 x 559.6mm)

Weight: 385lbs (175kg)

Chiller: 26.38 x 18.5 x 35.0"
(670 x 470 x 890mm); 202lbs (92kg)

Operational efficiency: 10.2 lumens per watt

Specifications: Up to 6,000:1 contrast | >95% of Rec. 2020 color gamut | Up to 47,000 lumens with HB lens, 35,000 lumens with UHC lens

Power consumption: 4,601 W including chiller, max DCI brightness, at 25 C 15,700 BTU/hr

Dimensions: 61.1 x 28.0 x 22.0"
(1551.1 x 710.6 x 559.6mm)

Weight: 385lbs (175kg)

Chiller: 26.38 x 18.5 x 35.0"
(670 x 470 x 890mm); 202lbs (92kg)

Operational efficiency: 14.5 lumens per watt

Specifications: Up to 6,000:1 contrast | >95% of Rec. 2020 color gamut | Up to 35,000 lumens

Power consumption: 2,394W, max DCI brightness at 25 C 8,200 BTU/hr

Dimensions: 37.2 x 28.0 x 20.7" (944 x 711 x 525mm)

Weight: 285lbs (130kg)

Operational efficiency: 14.3 lumens per watt

Specifications: Up to 6,000:1 contrast | >95% of Rec. 2020 color gamut | Up to 26,000 lumens

Power consumption: 1,820W, max DCI brightness at 25 C 6,280 BTU/hr

Dimensions: 37.2 x 28.0 x 20.7" (944 x 711 x 525mm)

Weight: 285lbs (130kg)

CP4420-RGB



Medium-screen auditoriums | Event cinema
Post production | Screening rooms

Operational efficiency: 12.6 lumens per watt

Specifications: Up to 6,000:1 contrast |

>95% of Rec. 2020 color gamut |

Up to 20,000 lumens

Power consumption: 1592W, max DCI brightness,
at 25 C 5400 BTU/hr

Dimensions: 37.2 x 28.0 x 20.7" (944 x 711 x 525mm)

Weight: 238lbs (108kg)

CP4415-RGB



Small-screen auditoriums | Boutique cinema
Post production | Screening rooms

Operational efficiency: 11.6 lumens per watt

Specifications: Up to 6,000:1 contrast |

>95% of Rec. 2020 color gamut |

Up to 15,000 lumens

Power consumption: 1,295W, max DCI brightness,
at 25 C 4,400 BTU/hr

Dimensions: 37.2 x 28.0 x 20.7" (944 x 711 x 525mm)

Weight: 238lbs (108kg)

CP2420-RGB



Medium-screen auditoriums | Event cinema
| Post production | Screening rooms

Operational efficiency: 12.9 lumens per watt

Specifications: Up to 6,000:1 contrast | >95% of
Rec. 2020 color gamut | 20,000 lumens

Power consumption: 1,545W, max DCI brightness
at 25 C 5,300 BTU/hr

Dimensions: 42.6 x 25.0 x 13.3"
(1083 x 635 x 337mm)

Weight: 176lbs max (80kg)

CP2415-RGB



Small-screen auditoriums | Boutique cinema
| Post production | Screening rooms

Operational efficiency: 12.7 lumens per watt

Specifications: Up to 6,000:1 contrast | >95% of
Rec. 2020 color gamut | 15,000 lumens

Power consumption: 1,177W, max DCI brightness
at 25 C 4,000 BTU/hr

Dimensions: 42.6 x 25.0 x 13.3"
(1083 x 635 x 337mm)

Weight: 174lbs max (79kg)

CP4420m-RGBH



Medium-screen auditoriums | Mainstream cinema | Post production | Screening rooms

Operational efficiency: 14.8 lumens per watt

Specifications: 0.98" 4K SST DMD | 6,000:1 contrast | DCI-P3 with more color options in the future | 20,000 lumens

Power consumption: 1,169W, max DCI brightness at 25 C 4,640 BTU/hr

Dimensions: 33.5 x 26.8 x 11.98" (850 x 680 x 304 mm)

Weight: 132lbs max (60kg)

CP4415m-RGBH



Medium-screen auditoriums | Boutique cinema | Post production | Screening rooms

Operational efficiency: 14.2 lumens per watt

Specifications: 0.98" 4K SST DMD | 6,000:1 contrast | DCI-P3 with more color options in the future | 15,000 lumens

Power consumption: 1060W, nominal, @25C 3620 BTU/hr

Dimensions: 33.5 x 26.8 x 11.98" (850 x 680 x 304 mm)

Weight: 132lbs max (60kg)

CP4410m-RGBH



Small-screen auditoriums | Event cinema | Post production | Screening rooms

Operational efficiency: 11.7 lumens per watt

Specifications: 0.98" 4K SST DMD | 6,000:1 contrast | DCI-P3 with more color options in the future | 10,000 lumens

Power consumption: 860W, nominal, at 25C 2930 BTU/hr

Dimensions: 33.5 x 26.8 x 11.98" (850 x 680 x 304 mm)

Weight: 132 lbs max (60 kg)

CP2411-RBe



Small-screen auditoriums | Boutique cinema | Screening rooms

Operational efficiency: 9.4 lumens per watt

Specifications: 2,000:1 contrast | > DCI-P3 color | up to 11,000 lumens

Power consumption: 1,169W, max DCI brightness at 25 C 4,000 BTU/hr

Dimensions: 27.4 x 27.1 x 15.9" (696 x 688 x 404mm)

Weight: 137lbs max (62kg)



CP2409-RBe



Small-screen auditoriums | Boutique cinema
| Screening rooms

Operational efficiency: 9.6 lumens per watt

Specifications: 2,000:1 contrast | > DCI-P3 color |
up to 9,000 lumens

Power consumption: 938W, max DCI brightness at 25 C 3,200 BTU/hr

Dimensions: 27.4 x 27.1 x 15.9"
(696 x 688 x 404mm)

Weight: 137lbs max (62kg)



CP2406-RBe



Small-screen auditoriums | Boutique cinema
| Screening rooms

Operational efficiency: 10.7 lumens per watt

Specifications: 2,000:1 contrast | > DCI-P3 color |
up to 9,000 lumens

Power consumption: 559W, max DCI brightness at 25 C 1,900 BTU/hr

Dimensions: 27.4 x 27.1 x 15.9"
(696 x 688 x 404mm)

Weight: 137lbs max (62kg)



CP4420-Xe



Medium-screen auditoriums | Event cinema
Post production | Screening rooms

Specifications: 2,000:1 contrast | DCI-P3 color |
up to 22,000 lumens

Power consumption: max DCI brightness at 25 C 14,300BTU/hr

Dimensions: 41.9" x 25.4" x 17.5"
(1064 x 644 x 446mm)

Weight: 256lbs max (116kg)



CP2420-Xe



Medium-screen auditoriums | Event cinema
Post production | Screening rooms

Specifications: >2,000:1 contrast | DCI-P3 color |
up to 22,000 lumens

Power consumption: max DCI brightness at 25 C 14,300 BTU/hr max

Dimensions: 41.9" x 25.4" x 17.5"
(1064 x 644 x 446mm)

Weight: 256lbs max (116kg)

CP2415-Xe



Small-screen auditoriums | Boutique cinema
Post production | Screening rooms

Specifications: 2,000:1 contrast | DCI-P3 color
| up to 15,000 lumens

Power consumption: max DCI brightness at 10,900
BTU/hr

Dimensions: 27 x 25 x 15" (687 x 665 x 395mm)

Weight: 122lbs max (55kg)

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
PH: +1 714-236-8610

Christie Digital Systems Canada
Inc.
Kitchener
PH: +1 519-744-8005

Worldwide offices

Australia
PH: +61 (0) 7 3624 4888

Brazil
PH: +55 11 3181-2952

China (Beijing)
PH: +86 10 6561 0240

China (Shanghai)
PH: +86 21 6030 0500

China (Shenzhen)
PH: +86 755 3680 7000

Colombia
PH: +57 (315) 652-9620

Germany
PH: +49 221 99 512-0

India
PH: +91 (080) 6708 9999

Mexico
PH: +52 (55) 4744-1791

Singapore
PH: +65 6877 8737

South Korea
PH: +82 2 702 1601

Spain
PH: +34 (0) 91 633 99 90

United Arab Emirates
PH: +971 (0) 4 503 6800

United Kingdom
PH: +44 (0) 118 977 8000

United States (Arizona)
PH: +1 602-943-5700

United States (Texas)
PH: +1 469-757-4420

For the most current specification information, please visit christiedigital.com

Copyright 2024 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
CD48001-CineLife+-line-card-update-Dec-25-EN



CHRISTIE