# Christie CP4325-RGB

Digital cinema Screening rooms Post production

# RealLaser illumination. Unmatched cinematic performance.

The Christie<sup>®</sup> CP4325-RGB pure laser cinema projector brings a premium movie-going experience to mainstream theatres. Featuring CineLife<sup>™</sup> electronics and RealLaser<sup>™</sup> illumination, this compact, all-in-one DCI-compliant projector excels in image quality and operational lifetime while providing a low cost of ownership. With the CP4325-RGB, exhibitors can impress audiences with incredibly colorful and detailed, true-to-life images while benefiting from an affordable platform that will perform well into the future.

## RealLaser. Real smart.

What sets Christie RealLaser apart? We've taken everything we know from being the preeminent manufacturer of RGB pure laser projectors and coupled it with the latest innovations in laser devices. The result is an incredibly efficient and long-lasting light source that drastically outperforms any other cinema illumination platform. The long, stable operational life of RealLaser powered projectors means they provide the lowest cost of ownership of any cinema projector in their class. Make bringing the art of exhibition to the next level a reality.



Specifications		Christie CP4325-RGB
Brightness	nominal	• Up to 23,000 lumens (<25°C ambient) <sup>1</sup>
	lifetime	<ul> <li>&gt;30,000 hours to 80% brightness (&lt;25°C ambient)</li> </ul>
Contrast ratio		• Up to 6000:1 <sup>2</sup>
Digital micromirro device	r	<ul> <li>1.38" Enhanced 4K 3-chip DMD DLP Cinema®</li> <li>4096 x 2160 (4K)</li> </ul>
Color gamut	native gamut	• >90% Rec 2020 coverage
Processing electronics		<ul> <li>Christie<sup>®</sup> CineLife<sup>™</sup> Series-3 (Series-2 IMB compatible - specific models)<sup>3</sup></li> <li>HDMI v1.4a x2 • 16-channel AES (RJ45 x2)</li> <li>2K120 / 4K48 fps (w/Christie IMB-S3) • Up to 4K120 upgradable</li> <li>Built-in automation controller • 3D Sync Connector (12V 1A powered)<sup>4</sup></li> </ul>
Lens mount configuration		<ul> <li>Fully motorized Intelligent Lens System (ILS™)</li> </ul>
Lenses		• 1.13-1.66 • 1.31-1.85 • 1.45-2.17 • 1.63-2.71 • 1.95-3.26 • 2.71-3.89 • 3.89-5.43 • 4.98-7.69
Input line voltage		• Single phase 220V
Power input requirements		<ul> <li>Input A: 200-240 VAC @ 50-60Hz, 17A, 3300W (11,260 BTU/hr)</li> <li>Input B (UPS input): 100-240 VAC @ 50/60Hz, 10A, 1000W</li> </ul>
Cooling		Liquid pressurized/TEC, self-contained • Heat extraction optional
Laser class		• Class 1 - Risk Group 3
Dimensions (w/o lens)	size	• (LxWxH): 37.2 x 28 x 21.8" (944 x 711 x 553mm)
	weight	• 285lbs (130kg)
Accessories		<ul> <li>Christie IMB-S3 (153-100102-01) • NAS-S3 8TB storage (153-101103-01)</li> <li>Rack mount pedestal (108-416102-01)</li> <li>Extraction duct adaptor (163-102104-01)</li> <li>Rack mount pedestal adaptor (163-101103-01)</li> </ul>

<sup>1</sup> With existing high brightness cinema lens

<sup>2</sup> With new UHC lens suite

<sup>3</sup> Series-2 IMB model compatibility subject to change. Currently supports Dolby IMS3000, GDC SX3000 / SX4000


<sup>4</sup> Supports all conventional 3D systems except "color separation" based 3D (i.e. 6P)

### Key features:


- Long-lasting, high-performance light source - Christie RealLaser illumination provides amazing color, extended contrast capabilities and over 30,000 hours of optimal brightness performance
- The pinnacle of image quality Expansive color gamut and contrast ratios up to 6,000:1 deliver unmatched presentation quality
- Christie CineLife electronics –
   Streamlined UX-designed interface for simple playback, scheduling and management of cinema content

- Future-proofed High Frame Rate capable: 4K 48fps or 2K 120fps performance out-of-the-box with upgrade path for 4K 120fps capabilities
- Compact form factor Fits seamlessly into existing booths for easy installation
- Backwards compatibility Compatible with existing accessories including the Christie Rack Mount Pedestal and cinema lenses for additional cost savings
- Fully sealed optics Protection from environmental contaminants to maintain optimal performance


#### Front view




Side view







Back view



United Kingdom Branch & EMEA Head Office ViewPoint 200 Ashville Way Wokingham Berkshire, U.K. RG41 2PL PH: +44 (0) 118 977 8000 Middle East Light Industrial Unit (LIU-17) Nad Al Shibba Sheikh Mohammed Bin Zayed Road Dubai Silicon Oasis PO Box: 293762 Dubai - U.A.E PH: +971 (0) 4 503 6800 Africa Unit C3 Northlands Deco Park New Market Road Northriding Randburg 2164 Johannesburg Gauteng South Africa PH: +27 11 251 0000 
 Other EMEA offices

 Germany

 Branch Office

 PH: +49 2161 566 200

 France

 Branch Office

 PH: +33 (0) 141 21 44 04

**Spain** Branch Office PH: +34 91 633 9990

PH: +34 91 633 9990 Italy Independent Sales Consultant Office

PH: +39 (0) 2 9902 1161 **Russia** Independent Sales Consultant Office PH: +7 (495) 930-8961





#### For the most current specification information, please visit www.christieemea.com

Copyright 2018 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4620 Dec 17

