CHRISTIE D4K40-RGB

Giant screens | Large-scale events and venues | Planetariums and domes Projection mapping | Sports venues | Theme parks and attractions

Pure laser. Pure performance. Pure excellence.

Take large-scale projection to new heights with the Christie[®] D4K40-RGB. This all-in-one, 45,000 lumen RGB pure laser projector raises the bar for design, image quality and processing. Featuring Christie Real|Laser™ illumination technology and TruLife[™] electronics, the D4K40-RGB is a powerhouse projector engineered to light up the largest canvases with spectacular visuals.

All-in-one design

What sets the Christie D4K40-RGB apart? Thanks to our engineering expertise, we designed the smallest and lightest high-brightness, large venue RGB laser projector available. There are no heavy external chillers, remote laser racks, or special pedestals - everything is completely integrated into a single chassis.

Spectacular visuals

Our proprietary RGB pure laser illumination source provides an exceptionally wide color gamut and when combined with TruLife electronics and 4K resolution, allows the D4K40-RGB to reveal amazing depth of detail. Add optional high frame rate (HFR) capabilities up to 120fps, 5000:1 On/Off contrast ratio, omnidirectional capabilities, and the D4K40-RGB sets the new standard for large-scale projection.



Technical specifications		Christie D4K40-RGB
Image	brightness	 45,000 ISO lumens 40,000 ANSI lumens (typical) @ 25°C 41,000 center lumens (typical) @ 25°C
	contrast	• 5000:1 On/Off ¹
Display technology	type	• 3DLP® 1.38" sealed to the prism
	resolution	• 4096 × 2160 (4K)
Illumination	type	• RGB (red, green & blue) pure laser
	performance	• 25,000 hours ²
Orientation		Omnidirectional
Image processing		Christie TruLife electronics, 1.2Gpx/s
Frame rates		 24-60Hz standard Optional 96-120Hz 4K, 240-480Hz 2K scaled
Inputs	standard	 2 x 12G-SDI1 x HDMI 2.0 1 x DisplayPort 1.2 (HBMIC) 1 x Fiber (QSFP+) for use with Christie Link Transmitter HDBaseT
	optional	 Dual 3G SD/HD-SDI input card Dual Link DVI input card Quad DisplayPort input card Twin HDMI input card Terra (SDVoE) input card
Warping and blending	standard	• Christie Twist™
	optional	 Christie Twist Premium and Twist Pro Christie Mystique[®] Christie Guardian
Lenses (available in standard and high contrast)		 0.72:1 0.9:1 1.13-1.31:1 1.31-1.63:1 1.63-2.17:1 1.99-2.71:1 2.71-3.89:1 3.89-5.43:1 (not available in the USA)
Input line voltage		Single phase 220 VAC, 19A, 4000W, 13,650 BTU/hr Connector: 30A IEC309
Cooling		• Liquid, self-contained
Laser class		Class 1 – Risk Group 3
Operating environment		 5-40°C (41-104°F) Relative humidity: 10-80% non-condensing
Dimensions	size	• (LxWxH): 37 x 28 x 21.8" (947 x 711 x 553mm) not including lens
	weight	• 285lbs (130kg)

¹ Using high contrast lens.

² To 50% brightness.

Key features

- All-in-one, compact design No external chillers, laser racks or parts, and a manageable weight of 285lbs makes it the smallest and lightest high-brightness laser projector available
- Omnidirectional Operates in any orientation for unlimited installation flexibility
- Christie TruLife electronics Delivers native 4K resolution, high frame rate video up to 240fps for unprecedented image fidelity
- High contrast Achieves 5,000:1 On/Off contrast for amazing depth of detail

- > Expanded color gamut Produces >95% of the Rec. 2020 color space for rich, vibrant and true-to-life visuals
- Energy efficient Operates on 220V single-phase power for lower cost of ownership
- Christie Twist Built-in image warping and multi-projector blending software
- > 4K lens compatibility Compatible with most Christie 4K lenses
- Field replaceable RGB laser light source Provides easy service and replacement of the laser light source

For the most current specification information, please visit christiedigital.com

Copyright 2023 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD3926-Christie-D4K40-RGB-Datasheet-Sept-23-EN



