## **Christie E500 Controller**

## **Technical specifications**

	specifications	
Inputs		<ul> <li>1 x DVI (HDCP compatible)</li> <li>1 x HDMI (HDCP compatible)</li> <li>1 x BNC SDI-in</li> <li>1 x BNC SDI-loop</li> </ul>
GenLock		• 1 x BNC in • 1 x BNC loop
Outputs		4 x RJ45     2 x BNC primary signal     2 x BNC backup signal
Control		<ul> <li>1 x DB-9 RS232</li> <li>1 x RJ45 Ethernet</li> <li>1 x USB-A link-in</li> <li>1 x USB-B link-out</li> <li>USB-B (front panel)</li> </ul>
Accessories		USB cable (1.5m) DVI cable (1.5m) Ethernet cable (1.5m)
Power	input rating	• 100-240 VAC @ 50/60Hz
	power consumption	• 20W
	heat output	• 68 BTU/hr
Physical	size	• (LxWxH) 19.2 x 13.5 x 3.5" (487 x 343 x 88mm)
	weight	• 11.7lb (5.3Kg)
Environment	operating temperature	• 32-104°F (0-40°C)
	operating humidity	• 10-90%
	storage temperature	• -14-122°F (-10-55°C)
Warranty		Three year parts and labor limited warranty Contact an authorized Christie representative for full details of our limited warranty

Performance specifications are typical. Due to constant research, specifications are subject to change without notice.

For the most current specification information, please visit christie digital.com  $\,$ 

Copyright 2023 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD3931-Christie-E500-Controller-Specsheet-Sept-23-EN

