


Christie FHD553-XU

Ultra-narrow bezel 55" LCD display

Technical specifications		Christie FHD553-XU	
Display technology	screen size (diagonal)	• 55"	
	native resolution	• 1920 x 1080	
	backlight	• Direct-lit LED	
	LED lifespan	• 50,000 hrs (50% brightness)	
	pixel pitch	• 0.63 x 0.63mm	
	bezel size	• 3.5mm combined nominal bezel to bezel	
	brightness	• 500 nits (cd/m ²) typical	
	contrast ratio (full field)	• 1400:1	
	viewing angle (CR 10:1)	• 178° h/v	
	refresh rate	• 50/60Hz	
	response time	• 8 ms	
	color space (CIE 1931)	• 72%	
	display colors	• 1.07 billion, 10 bit	
	Signal	inputs	• DisplayPort (Ver 1.2, HDCP) • 2 x HDMI (Ver 1.4, HDCP) • DVI-D (HDCP) • VGA
		outputs	• DisplayPort (daisy chains DisplayPort, HDMI, and DVI inputs up to 16 panels from one source). Built-in processing supports scaling video walls up to 10x10
Control	inputs	• RS-232 via D-Sub9 • RJ-45 LAN • Keypad • IR window • IR wire extender	
	outputs ²	• RJ-45 for control looping	
Power	input rating	• 100-240 VAC @ 50/60Hz	
	power consumption	• 165W typical • 220W maximum • ≤0.5W standby	
Environment	operating temperature	• 41-95°F (5-35°C)	
	operating humidity	• 20-90% non-condensing	
	storage temperature	• -4-140°F (-20-60°C)	
Physical		Dimensions (WxHxD)	
	panel only (without handles)	• 47.78 x 26.94 x 3.88" (1213.5 x 684.3 x 98.5mm)	
	panel mount locations	• VESA standard (WxH) 400 x 400mm, M8	
Runtime	• Designed for 24/7 operation ¹ , featuring a reliable power supply and cooling system		
Features	<ul style="list-style-type: none"> • Commercial-grade LCD with LED backlight • Standard size OPS • Christie® Phoenix® EP supported • Built-in processing supports video walls up to 10x10 • Multi-stream transport supported across up to four panels (UHD at 60 fps) • Anti-glare coating • SNMP for monitoring • Remote and button lock • Pixel Orbiting (IRFM) • Bezel compensation • Kensington lock • Staggered power-up 		
Accessories	<ul style="list-style-type: none"> • Panel ships with DisplayPort cable, IR remote control, external IR receiver, power cable, control daisy chain cable, rear alignment brackets, user manual • Optional wall mount: Christie MPL15 6-axis mount for portrait or landscape 		
Warranty	<ul style="list-style-type: none"> • Three years parts and labor limited warranty • Contact an authorized Christie representative for full details of our limited warranty 		

¹ Avoid static images for extended periods. Refer to the product documentation for additional guidance.
² Does not include OPS power draw.

Content and operating conditions can affect the useful life of the product. Please refer to the product documentation and Christie Operating Guidelines for Flat Panels, available at www.christiedigital.com



United Kingdom
 Branch & EMEA
 Head Office
 ViewPoint
 200 Ashville Way
 Wokingham
 Berkshire, U.K.
 RG41 2PL
 PH: +44 (0) 118 977 8000

Middle East
 Light Industrial Unit (LIU-17)
 Nad Al Shibba
 Sheikh Mohammed Bin Zayed Road
 Dubai Silicon Oasis
 PO Box: 293762
 Dubai - U.A.E
 PH: +971 (0) 4 503 6800

Africa
 Unit C3
 Northlands Deco Park
 New Market Road
 Northriding
 Randburg
 2164
 Johannesburg
 Gauteng
 South Africa
 PH: +27 11 251 0000

Other EMEA offices

Germany
 Branch Office
 PH: +49 2161 566 200

France
 Branch Office
 PH: +33 (0) 1 41 21 44 04

Spain
 Branch Office
 PH: +34 91 633 9990

Italy
 Independent Sales Consultant Office
 PH: +39 (0) 2 9902 1161

Russia
 Independent Sales Consultant Office
 PH: +7 (495) 930-8961



For the most current specification information, please visit www.christieemea.com

Copyright 2017 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4555 Aug 17

CHRISTIE®