


Christie LX602

Compact, easy-to-install, value-added 3LCD projector




Technical specifications		Christie LX602
Image	brightness (lumens)	• 6200 ISO • 5475 ANSI
	dynamic contrast	• 10,000:1
Display technology	type	• 3 x 0.63" Inorganic LCD
	native resolution	• 1024 x 768 XGA
Lamp	type	• 1 x 300W UHB
	typical lifetime	• Standard mode: up to 4000 hrs • Eco mode: up to 6000 hrs
Inputs	signals	• VGA/SVGA/XGA/WXGA/WXGA+/SXGA/SXGA+/WSXGA+/UXGA/WUXGA/MAC 16" • NTSC, NTSC4.43, PAL, PAL-M, PAL-N, SECAM 480i • 480p, 576i, 720p, 1080i, 1080p
	scan rates	• Horizontal: 32-106kHz • Vertical: 56-120Hz
	standard	• Computer Input: 15-pin D-sub x 1 • Digital Input: HDMI x 2 • Video Input: Composite video RCA jack x 1, Component video 15-pin D-sub x 1 • Audio Input: 3.5mm stereo mini jack x 1, RCA jack (L/R) x 1 • USB Type A x 1 (for wireless network)
Outputs		• HDMI x 1 • 15-pin D-sub x 1 • Audio output 3.5mm stereo mini jack x 1
Control and networking		• 9-pin D-sub x 1 (RS-232C) • RJ45 port
Accessories	standard	• IR remote • AC line cords for projector head • RGB cable • Adapter cover • Lens covers • User documentation
	optional	• Ceiling mount (108-506102-01) • 300W UHB lamp (003-005852-01) • Air filter (003-005853-01) • USB wireless adapter (121-116109-XX)
Lens	adjustment	• Zoom, focus and lens shift
	lens	• 1.4-2.3:1, 1.6x manual zoom
Power requirements	operating voltage	• 100-120 VAC @ 50/60Hz • 220-240 VAC @ 50/60Hz
	consumption	• 440W @ 100 -120 VAC • 420W @ 220-240 VAC
	operating current	• 4.4A @ 100 VAC • 2.2A @ 220 VAC
	dissipation	• 1502 BTU/hr @ 100-120 VAC • 1433 BTU/hr @ 200-240 VAC
Audible noise		• Standard mode: 39dB(A) • Eco mode: 30dB(A)
Physical	size	• (LxWxH) 13.3 x 18.3 x 5.4" (338 x 466 x 138mm) w/o feet
	shipping size	• (LxWxH) 18.8 x 22 x 9.7" (478 x 560 x 246mm)
	weight	• 15.2lbs (6.9kg)
	shipping weight	• 21.8lbs (9.9kg)
Operating environment	temperature	• 32-104°F (0-40°C)
	altitude	• 0-10,000ft (3048m)
	humidity	• 10-85% non-condensing
Key features		• Long-life lamp up to 6000 hrs (eco mode) • AMX and Crestron connectivity • Hybrid filter up to 10,000 hrs • DICOM simulation mode • HDCR • Picture-in-Picture/Picture-by-Picture • Edge blending • Warping • Zoom, focus, H/V lens shift • HDMI-Out • Closed caption • Built-in keypad • 3D Keystone • Wireless capable • 16W built-in audio
Regulatory		• Directives: RoHS • REACH • WEEE • UL/CSA/IEC 60950-1 • FCC Class A • CCC • CEL (GB32028-2015) • CECP (CQC6102-2016)
Warranty		• Three years on the projector • Contact an authorized Christie representative for full details of our limited warranty


Front view




Side view



Top view



Back view



Christie® support and services

All Christie products are backed by industry-leading warranties, renowned service and support. We ensure our customers are well supported with training, service and technical knowledge through our extensive distribution and support network.

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
ph: 714 236 8610
Christie Digital Systems Canada Inc.
Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888
Brazil
ph: +55 (11) 2548 4753
China (Beijing)
ph: +86 10 6561 0240
China (Shanghai)
ph: +86 21 6278 7708
Columbia
ph: +57 (318) 447 3179
Eastern Europe
ph: +36 (0)1 47 48 138

France
ph: +33 (0) 1 41 21 44 04
Germany (Cologne)
ph: +49 221 99 512-0
Germany (Moechengladbach)
ph: +49 2161 566200
India
ph: +91 (080) 6708 9999
Japan
ph: +81 3 3599 7481
Mexico
ph: +52 55 4744 1790

Republic of South Africa
ph: +27 11 251 0000
Singapore
ph: +65 6877 8737
South Korea
ph: +82 2 702 1601
Spain
ph: +34 91 633 9990
United Arab Emirates
ph: +971 (0) 4 503 6800
United Kingdom
ph: +44 (0) 118 977 8000

United States (Arizona)
ph: 602 943 5700
United States (New York)
ph: 646 779 2014

Independent sales consultant offices

Italy
ph: +39 (0) 2 9902 1161
Russia
ph: +7 (495) 930 8961



For the most current specification information, please visit www.christiedigital.com

Copyright 2017 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.
Printed in Canada on recycled paper. 4617 Dec 17

CHRISTIE®