INTEGRATED SOLUTIONS FOR GIANT SCREENS

Immerse your audience in spectacular visuals





CHKISTIE

GIVE THEM WHAT THEY WANT

Christie[®] can specify an integrated projection solution to meet your technical requirements, scale to your specific environment and fit your budget. Whether you're looking for a single projector or a multichannel system, Christie[®] has an array of solutions that provide the brightness, contrast, resolution and image uniformity your venue needs.

The display technology is just one part of an integrated solution. Our powerful Christie Mystique® auto-alignment software and Pandoras Box® processing and show control tools keep your projection system performing optimally.

- No surprise extras: Projection system design, installation and commissioning are included in our quotation.
- > Worry-free investment: Our five-year warranty ensures you have peace of mind.
- No mandatory service contracts : You are in charge. Choose from a range of service and support options.
- Financing: We are happy to work with you on the purchase model that best suits your institutional needs.

Christie Eclipse,
 Christie Mirage SST
 & Christie D4K40-RGB



CHRISTIE

National Naval Aviation Museum

CHRISTIE D4K40-RGB

All-in-one, 40,000 lumen, 4K projectors with no external chillers or laser racks. Add high frame rate capabilities up to 120fps at 4K, 5000:1 On/Off contrast ratio, omnidirectional capabilities, and the 4K40-RGB models set a new standard for large-scale projection.





These are examples of integrated solutions using D4K40-RGB. Final system specifications are subject to customer requirements and environment.


Contact your Christie representative for a detailed proposal.

		1 Channel	2 Channel	3 Channel
Components included	Projector	• D4K40-RGB		
	Lens	• 0.9:1 high contrast		
	Quantity	• 1	• 2	• 3
	Content delivery	Christie [®] Pandoras [®] Box	<	
	Alignment solution	• No	Christie Mystique®	
	Projector stand	• Yes		
	AV rack	• Yes		
	Projection management and design	• Included		
	Installation and commissioning	Included		
Main display	Brightness (at 90% power)	• <10.2 fL	• <10.4 fL	• <18.5 fL
	Contrast (projector + lens)	• <5000:1		
	Native resolution	• 8.8 megapixels	• 12.6 megapixels	• 22.4 megapixels
	Aspect ratio	• 17:9	• 4:3	
	Frame rate (standard)	• 24-60Hz		
	Frame rate (optional)	• 96-120Hz 4K or 240-480Hz 2K		
Content delivery	Server storage	• <14.4TB		
	Video inputs for alternate content	 Included: Dual HDMI (supports HDMI 2.0 and HDMI 1.4) Optional¹: Quad 3G SDI, Dual DP 1.2 or Dual DVI² 		
Physical	Screen dimensions	• 70'(cord) x 38'	• 70' (cord) x 52.5'	
	Screen gain	•1		
	Projector dimensions $(L \times W \times H)$	• 37" x 28" x 21.8" (947mm x 711mm x 553mm)		
	Power (per projector)	• 220 VAC, 19A, 4000W		
	Heat load (per projector)	• 13,650 BTU/hr		
Performance	Extended warranty	Five years parts and labor. See your Christie representative for details of our limited warranty.		
	Support options	• See your Christie representative for details about our service and support plans.		
Optional 3D projection	Active 3D system	The D4K40-RGB can be upgraded to Mirage 4K40-RGB to support active 3D stereoscopic operation. See your Christie representative for specifications and pricing.		
Optional cinema	DCI compliant inset	• Yes ³		

CHRISTIE MIRAGE SST

This 4K projection system features a fiber-coupled, ultra-compact and lightweight, omnidirectional projection head that provides unmatched system design flexibility. The Mirage SST delivers 50,000 lumens¹ and high frame rates of 120fps at 4K for detail-rich visuals and 3D processing.





These are examples of integrated solutions using Mirage SST. Final system specifications are subject to customer requirements and environment.

Contact your Christie representative for a detailed proposal.

		1 Channel	2 Channel	3 Channel	
Components included	Projector	• Mirage SST			
	Lens	• 0.9:1 high contrast			
	Quantity	• 1	• 2	• 3	
	Content delivery	Christie [®] Pandoras [®] Box			
	Alignment solution	No · Christie Mystique®			
	Projector stand	• Yes			
	AV rack	• Yes			
	Projection management and design	• Included			
	Installation and commissioning	Included			
Main display	Brightness (at 90% power)	• <12.7 fL	• <13 fL	• <23.1 fL	
	Contrast (projector + lens)	• <5000:1			
	Native resolution	• 8.8 megapixels	• 12.6 megapixels	• 22.4 megapixels	
	Aspect ratio	• 17:9	• 4:3		
	Frame rate (standard)	• 24-120Hz			
	Frame rate (optional)	• 240-480Hz 2K			
Content delivery	Server storage	• <14.4TB			
-	Video inputs for alternate content	 Included: Dual HDMI (supports HDMI 2.0 and HDMI 1.4) Optional²: Quad 3G SDI, Dual DP 1.2 or Dual DVI³ 			
Physical	Screen dimensions	• 70' (cord) x 38'	• 70' (cord) x 52.5'		
	Screen gain	• 1			
	Dimensions per channel (L x W x H)	 Projector: 26.9" x 23.5" x 12" (680mm x 597mm x 305mm) Laser unit: 30.6" x 31.7" x 25.7" (777mm x 804mm x 653mm) Chiller⁴: 23.3" x 14.8" x 38.4" (592mm x 377mm x 976mm) 			
	Power per channel	 Projector: 100-240 VAC @ 50-60Hz 5A Laser unit: 200-240 VAC @ 50-60Hz 24A Chiller⁴: 200-240 VAC @50-60Hz, single phase 			
	Heat load per channel	Projector: 2850 BTU/hr • Laser unit: essentially none • Chiller ⁴ : < 21,526 BTU/hr			
Performance	Extended warranty	• Five years parts and labor. See your Christie representative for details of our limited warranty.			
	Support options	• See your Christie representative for details about our service and support plans.			
Optional 3D projection	Active 3D system	 Mirage SST supports active 3D stereoscopic operation. See your Christie representative for system specifications and pricing. 			
Optional cinema	DCI compliant inset	• Yes ⁵			

¹Lower brightness capabilities of 18,000 and 35,000 lumens are also offered. ²A second input card can be added at an additional cost.

³DVI is limited to 8-bit. ⁴Chiller dimensions and specifications may vary depending on country of deployment. ⁵Utilizing optional Christie CineLife™ Series projector.

CHRISTIE ECLIPSE

This true HDR 4K projection system offers a contrast ratio of up to 20,000,000:1, high frame rate capability, 26,000 lumens and an expansive color gamut that approaches the full Rec. 2020 / Rec. 2100¹ color space. Christie® Eclipse immerses audiences in a degree of detail and depth of color that have never before been possible with any Pro-AV projection system.



These are examples of integrated solutions using Christie Eclipse. Final system specifications are subject to customer requirements and environment.

Contact your Christie representative for a detailed proposal.



		1 Channel	2 Channel	3 Channel	
Components included	Projector	• Eclipse			
	Lens	• 0.9:1 high contrast			
	Quantity	• 1	• 2	• 3	
	Content delivery	• Christie® Pandoras® Box			
	Alignment solution	No · Christie Mystique®			
	Projector stand	• Yes			
	AV rack	• Yes			
	Projection management and design	• Included			
	Installation and commissioning	• Included			
Main display	Brightness (at 90% power)	• <8.8 fL	• <9.0 fL	• <16.0 fL	
	Contrast (projector + lens)	• <20,000,000:1			
	Native resolution	• 8.8 megapixels	• 12.6 megapixels	• 22.4 megapixels	
	Aspect ratio	• 17:9	• 4:3		
	Frame rate	• 24-120Hz			
Content delivery	Server storage	• <14.4TB			
-	Video inputs for	Included: Dual HDMI (supports HDMI 2.0 and HDMI 1.4)			
<u></u>	alternate content	Optional ² : Quad 3G SDI, Dual DP 1.2 or Dual DVI ³			
Physical	Screen dimensions	• 70' (cord) x 38'	• 70' (cord) x 52.5'		
	Screen gain	• 1			
	Dimensions per channel (L x W x H)	 Projector: 41.5" x 31" x 33.5" (1049mm x 784mm x 845mm) Laser unit: 30.6" x 31.7" x 25.7" (777mm x 804mm x 653mm) Chiller⁴: 23.3" x 14.8" x 38.4" (592mm x 377mm x 976mm) 			
	Power per channel	Projector: 200-240 VAC @50-60Hz, 15A, single phase • Laser unit: 200-240 VAC @50-60Hz, single phase • Chiller ⁴ : 200-240 VAC @50-60Hz, single phase			
	Heat load per channel	Projector: 7271 BTU/hr • Laser unit: essentially none • Chiller ⁴ : < 21,526 BTU/hr			
Performance	Extended warranty	• Five years parts and labor. See your Christie representative for details of our limited warranty.			
	Support options	• See your Christie representative for details about our service and support plans.			
Optional 3D projection	Active 3D system	• Eclipse supports active 3D stereoscopic operation. See your Christie representative for system specifications and pricing.			
Optional cinema	DCI compliant inset	• Yes ⁵			

¹To learn about the Rec. 2100 color space, visit <u>https://en.wikipedia.org/wiki/Rec._2100</u> ²A second input card carbe added at an additional cost. ³DVI is limited to 8-bit. ⁴Chiller dimensions and specifications may vary depending on country of deployment.

⁵Utilizing optional Christie CineLife™ Series projector.

CHRISTIE CINELIFE SERIES

The Christie[®] CineLife[™] Series is the most advanced lineup of cinema projectors available. Featuring the all-new UX-designed CineLife electronics platform, these RGB pure laser projectors enable the flawless delivery of brilliant cinematic experiences.

Our latest CP4440-RGB and CP4450-RGB CineLife+ models are capable of 4K 120fps high frame rate (HFR) playback and have ultra-fast processing of 1.06 Gigapixels per second.

Choose your DCI-compliant inset projector:

Christie offers a range of projectors to meet your resolution requirements, match your screen size and fit your budget.

	Christie CP4330-RGB	Christie CP4440-RGB	Christie CP4450-RGB
Resolution	• 4K	• 4K	• 4K
Brightness	• 28,000 lumens	• 45,000 lumens	• 55,000 lumens
Maximum screen size	• Up to 70' (21.3m)	• Up to 106' (32.3m)	• Up to 111' (33.8m)

Let's get started

Contact us today so we can collaborate with your team to determine the best projection solution for your budget and environment.

christiedigital.com/giantscreensolutions









For the most current specification information, please visit christiedigital.com

Copyright 2023 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP* and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD4003-Integrated Solutions-brochures-for-Giant-Screens-Feb-24-EN



