# Christie Apex Series


# 0.9mm indoor LED tiles - landscape

# **Technical specifications**


# Christie LED009-AL

Technical spec	ifications	Christie LED009-AL
Display technology	pixel pitch	• 0.96mm
	pixel configuration	• 3-in-1 (1R1G1B)
	pixel density	• 1,083,681 pixels/m <sup>2</sup>
	maximum calibrated brightness	• 800 nits (cd/m²)
	aspect ratio	• 16:9
	contrast ratio (full field)	• 5000:1
	viewing angle	• 160° H, 140° V
	refresh rate	• >_3200Hz
	scan rate	• 1/30
	color temperature	• 2700-9600K
	display colors	• 4.39 trillion (14-bit)
Signal	inputs	HDMI™ (HDCP) • DVI (HDCP) • HDSDI
Power	input rating - remote power supply <sup>1</sup>	• 100-240 VAC @ 50-60Hz
	power consumption per cabinet	• 75W typical • 223W maximum
	heat output	• 256 BTU/hr typical • 761 BTU/hr maximum
Environment	operating temperature	• 32-104°F (0-40°C)
	operating humidity	• 10-90% non-condensing
	storage temperature	• 14 -122°F (-10-55°C)
	environment	• Indoor
	IP rating	• 30
	LED lifespan (50% brightness)	• 100,000 hrs
	runtime	• 24/7
Physical	tile dimensions	• (WxHxD): 24.19 x 13.61 x 3.71"
		(614.4 x 345.6 x 94.3mm)
	tile area	• 2.29-ft <sup>2</sup> (0.2123m <sup>2</sup> )
	tile resolution	• 640 x 360 pixels
	tile weight	• 18.3lbs (8.3kg)
	tile array size to achieve 1920 x 1080	• 3x3
	cabinet design	Die-cast aluminum
	orientation	Landscape
	service access	All service from front
	module dimensions	• (WxH): 6.05 x 4.54" (153.6 x 115.2mm)
	module resolution	• 160 x 120 pixels
	installation options	• Flat • Concave
	additional required components	Remote power supply and controller
		sold separately
Certifications - current and pending <sup>2</sup>		• CE (Includes EMC), FCC, CSA (UL60950), RCM, IRAM-S, CCC, EAC, UKR, KC
Warranty		<ul> <li>Three years parts and labor limited warranty</li> <li>Contact an authorized Christie® representative for full details</li> <li>Extended warranty option available for a one-time fee at time of purchase</li> </ul>


### **Front view**



### **Back view**



### Side view



<sup>1</sup> See remote power supply specifications for full details.

<sup>2</sup> Certain of the listed certifications may be pending and not yet issued. For the current status of the listed certifications, please contact an authorized Christie representative.

For the most current specification information, please visit christiedigital.com

Copyright 2021 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and other countries. Performance specifications are typical. Due to constant research, specifications are subject to change without notice.

CD1809\_Christie Apex Series\_LED009\_Mar 2021 EN



