

Christie M Series - Mirage SXGA

		Mirage DS+6K-M 118-054100-XX	Mirage DS+10K-M 118-053109-XX	Mirage DS+14K-M 118-050117-XX
Image	brightness	<ul style="list-style-type: none"> • 6930 center lumens • 6300 ANSI lumens • 6800 ISO lumens 	<ul style="list-style-type: none"> • 11,550 center lumens • 10,500 ANSI lumens • 10,518 ISO lumens 	<ul style="list-style-type: none"> • 14,000 center lumens • 12,500 ANSI lumens • 13,750 ISO lumens
	contrast	<ul style="list-style-type: none"> • 2500:1 (full on/off) • 650:1 ANSI (typical) 	<ul style="list-style-type: none"> • 2500-10,000:1 (full on/off) • 650:1 ANSI (typical) 	<ul style="list-style-type: none"> • 2100:1 (full on/off) • 650:1 ANSI (typical)
	uniformity	<ul style="list-style-type: none"> • 90% brightness 		
Display	type	<ul style="list-style-type: none"> • 3DLP® 0.95" DMD 		
	native resolution	<ul style="list-style-type: none"> • SXGA+ (1400 x 1050) 		
Lamp	type	<ul style="list-style-type: none"> • Dual 200W P-VIP 	<ul style="list-style-type: none"> • Dual 350W P-VIP 	<ul style="list-style-type: none"> • Dual 450W NSH
	life	<ul style="list-style-type: none"> • High power: 2000 hrs @ 200W • Low power: 3000 hrs @ 150W 	<ul style="list-style-type: none"> • High power: 1500 hrs @ 350W • Low power: 2000 hrs @ 300W 	<ul style="list-style-type: none"> • High power: 1750 hrs @ 450W • Low power: 2000 hrs @ 360W
Inputs	standard	<ul style="list-style-type: none"> • Dual-link DVI-I input cards (x 2) with HDMI™ 1.3 receiver 	<ul style="list-style-type: none"> • Twin DisplayPort input card • 2 x Dual-link DVI +VGA 	
	optional	<ul style="list-style-type: none"> • Analog BNC • Dual-link DVI input card (330 MHz), VGA (165 MHz) • Dual SD/HD-SDI • Video decoder • Twin HDMI 	<ul style="list-style-type: none"> • Dual-link DVI • Dual SD/HD-SDI • Video decoder • Analog BNC • DMX512 interface 	
	input signals	<ul style="list-style-type: none"> • HDTV formats VGA through WQXGA (2560 x 1600) • 2D HDTV/DTV • HDMI 1.3 receiver, supports HDMI 1.4a 3D modes 	2D: <ul style="list-style-type: none"> • HDTV formats VGA through to QXGA (2048 x 1536) • Accepts all current HDTV/DTV formats • Multi-standard video decoder • Horizontal and vertical scaling (all inputs) 3D: <ul style="list-style-type: none"> • Native 3D 48-60Hz per eye • Frame doubled 3D 24-30Hz per eye • Dual input 3D 48-60Hz per eye • HDMI 1.4a Frame packed and Side-by-Side Horizontal 	
	pixel clock		<ul style="list-style-type: none"> • 330 MHz 	
	scan rates		<ul style="list-style-type: none"> • Horizontal: 15-120kHz • Vertical: 23.97-150Hz 	
Control and networking		<ul style="list-style-type: none"> • RS-232 in/out • RS-422 in • Ethernet (10/100) • GPIO (RS-232 9 Pin male connector) • Remote control (with optional wired XLR connection) 		
		<ul style="list-style-type: none"> • Built-in backlit LCD keypad • USB device • Slot 1-2 standard (populated): dual-link DVI-D (330 MHz) and VGA (165 MHz) 	<ul style="list-style-type: none"> • Built-in backlit LCD keypad • USB device 	
Optical system		<ul style="list-style-type: none"> • Dust sealed, 3-chip DMD light engine • Motorized horizontal and vertical lens offset • Scheimpflug (tilt) adjustment • Built-in light shutter • Tool-free lens insertion system 		
Lenses	fixed	<ul style="list-style-type: none"> • ILS lens 0.73:1 SX+/0.67:1 HD* • ILS lens 1.2:1 SX+/1.1:1 HD 	<ul style="list-style-type: none"> • ILS Lens 0.73:1 SX+* • ILS Lens 1.2:1 SX+ 	
	zoom	<ul style="list-style-type: none"> • ILS lens 1.25-1.6:1 SX+/1.16-1.49:1 HD** • ILS lens 1.5-2.0:1 SX+/1.4-1.8:1 HD • ILS lens 2.0-2.8:1 SX+/1.8-2.6:1 HD • ILS lens 2.8-4.5:1 SX+/2.6-4.1:1 HD • ILS lens 4.5-7.5:1 SX+/4.1-6.9:1 HD • ILS lens 7.5-11.2:1 SX+/6.9-10.4:1 HD 	<ul style="list-style-type: none"> • ILS Lens 1.25-1.6:1 SX+* • ILS Lens 1.5-2.0:1 SX+ • ILS Lens 2.0-2.8:1 SX+ • ILS Lens 2.8-4.5:1 SX+ • ILS Lens 4.5-7.5:1 SX+ • ILS Lens 7.5-11.2:1 SX+ 	
	offset	<ul style="list-style-type: none"> • All lenses ±100% Vertical ±50% Horizontal except those noted * 0.73:1 SX+/0.67:1 HD fixed lens ±23%V ±13%H ** 1.25-1.6:1 SX+/1.16-1.49:1 HD zoom lens ±70%V ±45%H 	<ul style="list-style-type: none"> • All lenses ±110% Vertical ±50% Horizontal except those noted * 0.67:1 fixed lens ±23%V ±13%H ** 1.16-1.49:1 zoom lens ±70%V ±45%H 	
Accessories	standard		<ul style="list-style-type: none"> • User manual • IR remote • Line cord • Two dual-link DVI-D cards • 3D sync cable 	<ul style="list-style-type: none"> • IR remote • Power cord • GPIO 3D sync cable
	optional		<ul style="list-style-type: none"> • Coarse dust filter • ILS lens adapter kit • Stacking frame dual HD/SDI input card • Twin HDMI input card • Video decoder input card¹ 	<ul style="list-style-type: none"> • Coarse dust filter • Fog juice filter • Ceiling mount • Ceiling mount extension • ILS lens adapter kit • Stacking frame • Christie® AutoStack™ • Christie AutoStack Premium

¹ May not include 3D support

Christie M Series - Mirage SXGA

	Mirage DS+6K-M 118-054100-XX	Mirage DS+10K-M 118-053109-XX	Mirage DS+14K-M 118-050117-XX	
Enhanced feature sets	<ul style="list-style-type: none"> • LiteLOC™ • Embedded Christie Twist™ - internal advanced warping and edge-blending 			
	<ul style="list-style-type: none"> • Electronically adjusted iris (manual or dynamic) • Dust-sealed, filter-free design • Reduced power requirements (as compared to competitive products on the market today) - at maximum brightness the unit only draws 870W; standby power consumption (phantom power draw) is less than 20W • Reduced noise levels • LCD keypad - active keys are amber to indicate whether function selected will be seen by the audience • Built-in portrait capabilities² 	<ul style="list-style-type: none"> • Contrast aperture • Dust-sealed, filter-free design • Reduced power requirements (as compared to competitive products on the market today) - at maximum brightness the unit only draws 1320W; standby power consumption (phantom power draw) is less than 20W • Reduced noise levels • LCD keypad - active keys are amber to indicate whether function selected will be seen by the audience • Built-in portrait capabilities² 	<ul style="list-style-type: none"> • Comprehensive Color Adjustment (CCA™) • Intelligent Lens System (ILS™) for zoom, focus, horizontal and vertical offset for all lenses • Menus in five languages • 99 channel memories • Auto setup • Digital keystone correction • 24/7 operation • Black level blending • Built-in portrait capabilities² 	
Power requirements	operating voltage	• 110-240 VAC 50/60Hz		
	operating current	• 9A @ 100 VAC	• 12A @ 100 VAC	• 15A @ 100 VAC
	dissipation	• 2971 BTU/hr	• 4508 BTU/hr	• 5118 BTU/hr
	power	• 870W	• 1320W	• 1500W
Dimensions	size	• (LxWxH): 22.1 x 19.7 x 10.2" (561 x 500 x 259mm)		
	shipping size	• 29 x 27 x 24.6" (737 x 689 x 625mm)		
	weight	• 55lbs (25kg) (without lens)		
	shipping weight	• 87lbs (39kg) (without lens)		
Operating environment	• Temperature: 40-104°F (5-40°C) • Humidity: 20-80% non-condensing			
Regulatory approvals	<ul style="list-style-type: none"> • UL/CSA/IEC 60,950 (3rd edition) • FCC Class A, CE, CCC RoHS • WEEE • This product conforms to all relevant European directives, standards, safety, health and environmental concerns • Directives (EC) 2011/65/EU (RoHS); 2012/19/EU (WEEE); Regulation (EC) No.1907/2006 (REACH) • CAN/CSA C22.2 No. 60950-1 • UL 60950-1 • IEC 60950-1 • FCC, Part 15, Subpart B, Class A • EN55022/CISPR22 Class A • EN55024 /CISPR24 • Certifications marks (check with Christie for latest update): cULus (Canada & US), CE (EU), CCC (China), EAC (Russia), KC (Korea), PSE (Japan), RCM (Australia & New Zealand), South Africa, Saudi Arabia, BIS (India) 			
Limited warranty	<ul style="list-style-type: none"> • Three years parts and labor (including light engine) • Contact an authorized Christie representative for full details of our limited warranty 			

² Christie M Series stacking frame is required in portrait orientation

Corporate offices

Christie Digital Systems USA, Inc.
Cypress
ph: 714 236 8610

Christie Digital Systems Canada Inc.
Kitchener
ph: 519 744 8005

Worldwide offices

Australia
ph: +61 (0) 7 3624 4888

Brazil
ph: +55 (11) 2548 4753

China (Beijing)
ph: +86 10 6561 0240

China (Shanghai)
ph: +86 21 6278 7708

France
ph: +33 (0) 1 41 21 44 04

Germany
ph: +49 2161 664540

India
ph: +91 (080) 6708 9999

Japan (Tokyo)
ph: 81 3 3599 7481

Korea (Seoul)
ph: +82 2 702 1601

Mexico
ph: +52 55-4744-1790

Republic of South Africa
ph: +27 11 251 0000

Russian Federation and Eastern Europe
ph: +36 (0) 1 47 48 100

Singapore
ph: +65 6877 8737

Spain
ph: +34 91 633 9990

United Arab Emirates
ph: +971 4 3206688

United Kingdom
ph: +44 (0) 118 977 8000

United States (Arizona)
ph: 602 943 5700

United States (New York)
ph: 646 779 2014

Independent sales consultant offices

Italy
ph: +39 (0) 2 9902 1161



For the most current specification information, please visit www.christiedigital.com

Copyright 2016 Christie Digital Systems USA, Inc. All rights reserved. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. Christie Digital Systems Canada Inc.'s management system is registered to ISO 9001 and ISO 14001. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. Printed in Canada on recycled paper. 4321 Nov 16

CHRISTIE